


## 4MP Indoor Pan & Tilt Wi-Fi Camera

### Uho-S2E-M4



## Features

- High quality image with 4MP, 1/3"CMOS sensor
- 4MP (2560\*1440)@25/20fps; 3MP (2304\*1296)@30/25fps; 2MP (1920\*1080)@30/25fps
- Ultra 265, H.265, H.264
- Built-in Mic & Speaker, support two-way audio, offer better interaction
- IR night vision, up to 10m (33ft) IR distance
- Support 512 G Micro SD card
- Wi-Fi connection and easy installation


## Specifications

| Model                      | Uho-S2E-M4                                                                                                                                                                                                        |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Camera                     |                                                                                                                                                                                                                   |
| Max Resolution             | 4 MP                                                                                                                                                                                                              |
| Sensor                     | 1/3.0"CMOS                                                                                                                                                                                                        |
| Min. Illumination          | Colour: 0.01 lux (F2.0, AGC ON)<br>0 lux with IR on                                                                                                                                                               |
| Day/Night                  | IR-cut filter with auto switch (ICR)                                                                                                                                                                              |
| Shutter                    | Auto/Manual, 1/4 to 1/100000 s                                                                                                                                                                                    |
| S/N                        | >52 dB                                                                                                                                                                                                            |
| WDR                        | DWDR                                                                                                                                                                                                              |
| Lens                       |                                                                                                                                                                                                                   |
| Focal Length               | 4.0 mm                                                                                                                                                                                                            |
| Iris                       | F2.0                                                                                                                                                                                                              |
| Field of View (H)          | 79.0°                                                                                                                                                                                                             |
| Field of View (V)          | 42.3°                                                                                                                                                                                                             |
| Field of View (D)          | 85.1°                                                                                                                                                                                                             |
| Iris Type                  | Fixed                                                                                                                                                                                                             |
| Illuminator                |                                                                                                                                                                                                                   |
| Illumination Distance (IR) | Up to 10m (33ft)                                                                                                                                                                                                  |
| Wavelength                 | 850 nm                                                                                                                                                                                                            |
| IR On/Off Control          | Auto/Manual                                                                                                                                                                                                       |
| Supplemental Light         | IR                                                                                                                                                                                                                |
| Video                      |                                                                                                                                                                                                                   |
| Video Compression          | Ultra 265, H.265, H.264                                                                                                                                                                                           |
| Frame Rate                 | Main Stream: 4MP (2560*1440), Max 25fps; 3MP (2304*1296), Max 30fps; 2MP (1920*1080), Max 30fps; 720P (1280*720), Max 30fps;<br>Sub Stream: 640*360,Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps; |
| Video Bit Rate             | 128 Kbps to 6144 Kbps                                                                                                                                                                                             |
| U-code                     | Support                                                                                                                                                                                                           |
| OSD                        | Up to 2 OSDs                                                                                                                                                                                                      |
| Privacy Mask               | Support (only NVR)                                                                                                                                                                                                |
| ROI                        | Up to 8 areas                                                                                                                                                                                                     |
| Video Stream               | Dual streams                                                                                                                                                                                                      |
| Image                      |                                                                                                                                                                                                                   |
| White Balance              | Auto, Outdoor, Fine tune, Sodium lamp, Locked, Auto2                                                                                                                                                              |
| Digital Noise Reduction    | 2D/3D DNR                                                                                                                                                                                                         |
| Smart IR                   | Support                                                                                                                                                                                                           |
| Dewarping                  | N/A                                                                                                                                                                                                               |
| HLC                        | N/A                                                                                                                                                                                                               |
| BLC                        | N/A                                                                                                                                                                                                               |
| Flip                       | Normal, Flip vertical, Flip horizontal, 180°                                                                                                                                                                      |

|                        |                                                                                                                    |
|------------------------|--------------------------------------------------------------------------------------------------------------------|
| Defog                  | Digital defog                                                                                                      |
| Events                 |                                                                                                                    |
| Basic Detection        | Human body detection, Motion detection, Audio detection                                                            |
| General Function       | IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication |
| Intelligent            |                                                                                                                    |
| Auto Tracking          | Support                                                                                                            |
| Audio                  |                                                                                                                    |
| Audio Compression      | G.711U, G.711A                                                                                                     |
| Audio Bitrate          | 64 Kbps                                                                                                            |
| Two-way Audio          | Support                                                                                                            |
| Suppression            | Support                                                                                                            |
| Sampling Rate          | 8 kHz                                                                                                              |
| Storage                |                                                                                                                    |
| Edge Storage           | MicroSD, up to 512 GB                                                                                              |
| Network Storage        | ANR                                                                                                                |
| Network                |                                                                                                                    |
| Wi-Fi                  | 2.4G Wi-Fi (IEEE802.11b/g/n), built-in antenna                                                                     |
| Protocols              | IPv4, TCP, UDP, DHCP, RTSP, DNS, DDNS, NTP, HTTP                                                                   |
| Compatible Integration | API                                                                                                                |
| Client                 | APP, Uniarch client                                                                                                |
| Web Browser            | Plug-in required live view: IE 10+, Chrome 45+, Firefox 52+, Edge 79+                                              |
| Wi-Fi                  |                                                                                                                    |
| Wireless Standards     | IEEE802.11b/g/n                                                                                                    |
| Frequency Range        | 2.4 GHz to 2.4835 GHz                                                                                              |
| Channel Bandwidth      | 20 MHz Support                                                                                                     |
| Modulation Mode        | 802.11b: CCK, QPSK, BPSK<br>802.11g/n: OFDM/HT                                                                     |
| Wi-Fi Security         | 64/128-bit WEP, WPA-PSK/WPA2-PSK                                                                                   |
| Transmit Power         | 802.11b: 17±1.5 dBm@11 Mbps802.11g: 14±1.5 dBm@54 Mbps802.11n: 12.5±1.5 dBm@150 Mbps                               |
| Receive Sensitivity    | 802.11b: -90 dBm@11 Mbps (Typical)802.11g: -75 dBm@54 Mbps (Typical)802.11n: -74 dBm@150 Mbps (Typical)            |
| Transmission Rate      | 802.11b: 11 Mbps802.11g: 54 Mbps802.11n: up to 150 Mbps                                                            |
| Interface              |                                                                                                                    |
| Audio I/O              | N/A                                                                                                                |
| Alarm I/O              | N/A                                                                                                                |
| Built-in Mic           | Support                                                                                                            |
| Built-in Speaker       | Support                                                                                                            |
| WIFI                   | Support                                                                                                            |
| Network                | 1 × RJ45 10 M/100 M Base-TX Ethernet                                                                               |
| Certification          |                                                                                                                    |
| EMC                    | CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035)<br>FCC (FCC 47 CFR part15 B)                           |

|                     |                                                                                            |
|---------------------|--------------------------------------------------------------------------------------------|
| RF                  | FCC ID (FCC CFR 47 part15 C)<br>CE RED (EN 301 489-1, EN 301 489-17, EN 300 328, EN 62311) |
| Safety              | CE LVD (EN 62368-1)                                                                        |
| Environment         | CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU);                                      |
| General             |                                                                                            |
| Power Consumption   | Max 6W                                                                                     |
| Power               | DC 5V/1.5A<br>Micro USB interface                                                          |
| Dimensions          | Φ80 x 120mm (Ø3.1" x 4.8")                                                                 |
| Weight              | 0.18kg(0.40lb)                                                                             |
| Working Environment | -10°C~55°C(-14°F ~ 131°F), Humidity: ≤95% RH (non-condensing)                              |
| Storage Environment | -10°C~55°C(-14°F ~ 131°F), Humidity: ≤95% RH (non-condensing)                              |
| Reset Button        | Support                                                                                    |
| LED Indicator       | 1, red/blue                                                                                |
| PTZ                 |                                                                                            |
| Number of Presets   | 20                                                                                         |
| Pan Range           | 0° ~ 340°                                                                                  |
| Pan Speed           | 17°/s ~ 50°/s<br>Preset speed: 50°/s                                                       |
| Tilt Range          | -5° ~ 55°                                                                                  |
| Tilt Speed          | 17°/s ~ 50°/s<br>Preset speed: 50°/s                                                       |

## Dimensions



## Accessories

### TR-WM05-A

Indoor Camera PTZ Wall Mount Bracket



### Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



[overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2024-2026 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

\*Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.