
4MP Mini 고정형 불릿 네트워크 카메라

IPC2124LB-ADF28(40)KM-H3





주요 특징

- 4MP, 1/3.0" CMOS 센서로 고화질 이미지 제공
- 4 MP (2560 × 1440)@25/20 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps; 720P (1280 × 720)@30/25 fps
- Ultra 265, H.265, H.264, MJPEG (서브 스트림 전용)
- 120dB 트루 WDR 기술로 강한 조명 환경에서도 선명한 이미지 구현
- 9:16 복도 모드 지원
- 스마트 IR, 최대 30m(98.4ft) IR 거리
- 내장 마이크
- MicroSD, 최대 512GB 지원
- IP67
- PoE 전원 공급 지원

사양

Model	IPC2124LB-ADF28KM-H3	IPC2124LB-ADF40KM-H3
카메라		
최대 해상도	4 MP	
센서	1/3.0" CMOS	
최저 조도	Color: 0.01 Lux (F2.0, AGC ON), 0 Lux with IR	
주간/야간	IR-cut filter with auto switch (ICR)	
셔터	Auto/Manual, 1 ~ 1/100000s	
조정 각도	Pan: 0° to 360°, Tilt: 0° to 90°, Rotate: 0° to 360°	
S/N	>52 dB	
WDR	120 dB	
렌즈		
초점 거리	2.8 mm	4.0 mm
아이리스	F2.0	
화각(수평)	97.8 °	76.3 °
화각(수직)	55.7 °	43.0 °
화각(사각)	110.8 °	88.8 °
Iris Type	Fixed	
DORI		
DORI 거리(렌즈)	2.8 mm	4 mm
DORI 거리(감지)	63.0 m (206.6 ft.)	90.0 m (295.2 ft.)
DORI 거리(관찰)	25.2 m (82.7 ft.)	36.0 m (118.6 ft.)
DORI 거리(인식)	12.6 m (41.3 ft.)	18.0 m (59.0 ft.)


DORI 거리(식별)	6.3 m (20.7 ft.)	9.0 m (29.5 ft.)
조명		
조명 거리(IR)	30 m (98.4 ft.)	
파장	850 nm	
IR 켜짐/꺼짐 컨트롤	Auto/Manual	
보조 조명	IR	
비디오		
비디오 압축	Ultra 265, H.265, H.264, MJPEG (Sub Stream Only)	
H.264 코드 프로파일	Baseline profile, Main profile, High profile	
프레임 속도	Main Stream: 4 MP (2560 × 1440), max. 25 fps; 3 MP (2304 × 1296), max. 30 fps; 1080P (1920 × 1080), max. 30 fps; 720P (1280 × 720), max. 30 fps Sub Stream: 720P (1280 × 720), max. 30 fps; D1 (720 × 576), max. 30 fps; 640 × 360, max. 30 fps; 2CIF (704 × 288), max. 30 fps; CIF (352 × 288), max. 30 fps;	
비디오 비트 전송률	128 Kbps to 6144 Kbps	
OSD	Up to 4 OSDs	
프라이버시 마스크	Up to 4 areas	
ROI	Support	
U-code	Support	
비디오 스트림	Dual streams	
이미지		
화이트 밸런스	Auto, Outdoor, Fine tune, Sodium lamp, Locked, Auto2, Area white balance	
디지털 노이즈 제거	2D/3D DNR	
스마트 IR	Support	
이미지 회전	Normal, Flip vertical, Flip horizontal, 180°, 90° Clockwise, 90° Anti-clockwise	
HLC	Support	

디워핑	N/A
BLC	Support
디포그	Digital defog
이벤트	
기본 감지	Motion detection, Ultra motion detection (human/ vehicle detection) , Tampering alarm, Audio detection
기본 기능	Watermark, IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication
오디오	
오디오 압축	G.711U, G.711A, AAC-LC
오디오 비트레이트	G.711U/G.711A: 64 kbps, AAC-LC: 128 kbps
양방향 오디오	N/A
억제	Support
샘플링 주파수	G.711U/G.711A: 8 kHz, AAC-LC: 8 kHz, 16 kHz, 48 kHz
저장 장치	
엣지 스토리지	MicroSD, up to 512 GB
네트워크 스토리지	ANR, NAS (NFS)
네트워크	
프로토콜	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL/TLS, SNMP, IPv6
호환성 통합	ONVIF (Profile S, Profile G, Profile T), API, SDK
고객	EZStation, APP
웹 브라우저	Plug-in required live view: IE 10+, Chrome 45+, Firefox 52+, Edge 79+, Plug-in free live view: Chrome 57+, Firefox 58+, Edge 16+
보안	Password Protection, Strong Password, HTTPS Encryption, Export Operation Logs, Basic and Digest Authentication for RTSP, Digest Authentication for HTTP, TLS 1.2, WSSE and Digest Authentication for ONVIF


사용자/호스트	Up to 32 users. 3 user levels: administrator, common user and operator
인터페이스	
오디오 I/O	N/A
알람 I/O	N/A
시리얼 포트	N/A
내장 마이크	Support
내장 스피커	N/A
WIFI	N/A
네트워크	1 × RJ45 10 M/100 M Base-TX Ethernet
비디오 출력	N/A
인증	
보호	IP67 (IEC 60529)
EMC	CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 50130-4) FCC (FCC 47 CFR part15 B)
안전성	CE-LVD (EN 62368-1) UL/CUL (UL 62368-1, CAN/CSA C22.2 No. 62368-1)
환경	CE-RoHS (2011/65/EU ; (EU) 2015/863) ; WEEE (2012/19/EU)
일반	
전원	DC 12 V±25%, PoE (IEEE 802.3af)
전력 소비량	Max. 3.6 W
전원 인터페이스	Ø5.5 mm coaxial power plug
크기	166 mm × 63 mm × 62 mm (6.5" × 2.5" × 2.5") (L × W × H)
무게	0.39 kg (0.86 lb.）
작업 환경	-30 ℃ to 60 ℃ (-22 ℉ to 140 ℉), Humidity: ≤ 95% RH (non-condensing)

저장 환경	-30 ℃ to 60 ℃ (-22 ℉ to 140 ℉), Humidity: ≤ 95% RH (non-condensing)
서지 보호	4 KV
초기화 버튼	N/A
재료	Graphene + Metal
웹 클라이언트 언어	5 Languages: English, Russian, Spanish, Vietnamese, Turkish

크기



액세서리

TR-JB05-A-IN Bullet Junction Box(Support Wiring From Behind,Square)	**TR-UP06-B-IN** Bullet Pole Mounting Bracket	**TR-A01-IN** NPT 3/4'' Waterproof Cable Gland
		
TR-UP06-C-IN-V2 Pole Mounting Bracket For Bullet Junction Box Only	**TR-UC08-C-V2** Bullet&Dome Corner Mounting Bracket	
		

Unlimited New View

Zhejiang Uniview Technologies Co., Ltd.

http://www.uniview.com

overseasbusiness@uniview.com; globalsupport@uniview.com

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

©2026 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.
*Product specifications and availability are subject to change without notice.
© 2022 Zhejiang Uniview Technologies Co., Ltd. 무단 전재 및 재배포 금지. *제품 사양 및 재고는 사전 예고 없이 변경될 수 있습니다.