

Unmanaged Ethernet PoE Switches NSW2020-8T2GT-LPOE-IN



Features

- Multiple working modes to address your business needs: Default (Normal mode), EXTEND (Surveillance mode)
- Support port traffic control
- Support for secure mode, all downlink ports can communicate only with uplink ports
- Up to 250m transmission distance on surveillance mode
- Support buffer optimization
- All metal housing, safe and reliable

Specifications

Model	NSW2020-8T2GT-LPOE-IN
Hardware Specification	
Ports Type	8×10/100Mbps PoE ports (RJ45),
	2×10/100/1000Mbps ports
Switching capacity	5.6 Gbps
Packet Buffer	2 M bit
MAC	4K
Forwarding performance	4.17Mpps
Prior Ports	1 to 2
Standards	IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at
Power Supply	AC: 100 to 240V, 50/60Hz
PoE Standard	IEEE 802.3 at, IEEE 802.3af
PoE Mode	ModeA (1236), ModeB (4578)

1



Max.PoE Power	Max capacity:65W Max capacity for single port: 30W
Max.Power	75W
Cooling Fans	0
Dimensions (W×D×H)	169*132*40mm
Operating Temperature	0°C to 40°C (32°F to 104°F)
Operating Humidity	10% to 90% (noncondensing)
Indicator	Power: Off: Abnormal power input.Green: Normal power input.Yellow: The total PoE power is higher than 85% of the total power of the device.LINK/ACT: Off: No linkSteady on: LinkedFlashing: Transmitting data
Weight	0.67KG
Working Mode	Default (Normal mode): All ports can communicate with each other, EXTEND (Surveillance mode): Transmission distance up to 250 meters

Ordering Info

Product Model	Description
NSW2020-8T2GT-LPOE	Unmanaged Ethernet Switch(PoE)

Zhejiang Uniview Technologies Co., Ltd.



http://www.uniview.com



overseasbusiness@uniview.com; globalsupport@uniview.com



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China (Zhejiang) Pilot Free Trade Zone, China



 $@2023\hbox{-}2025\ \hbox{Zhejiang Uniview Technologies Co., Ltd. All rights reserved.}\\$

^{*}Product specifications and availability are subject to change without notice.

^{*}Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.