

# 4MP ColorHunter with Wise-ISP Fixed Dome Network Camera IPC3524LE-ADF28(40)K-WP



## Features

- High quality image with 4 MP, 1/1.8" CMOS sensor and F1.0 large aperture lens
- 4 MP (2688 × 1520)@25/20 fps; 4 MP (2560 × 1440)@25/20 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
- Ultra 265, H.265, H.264, MJPEG
- Intelligent perimeter protection, including cross line, intrusion
- Based on target classification, the intelligent intrusion prevention system significantly reduces false alarms caused by leaves, birds, and lights, accurately focusing on humans and motor vehicles
- ColorHunter with Wise-ISP technology ensures 24-hour full-color images
- 120 dB true WDR technology enables clear image in strong light scene
- Supports 9:16 corridor mode
- Built-in mic
- White light, up to 30 m (98.4 ft.) warm light distance
- MicroSD, up to 512 GB
- IP67 protection
- IK10 protection
- Supports PoE power supply
- 3-axis


## Specifications

| Model                              | IPC3524LE-ADF28K-WP  | IPC3524LE-ADF40K-WP |
|------------------------------------|--|---------------------|
| <b>Camera</b>                      |  |                     |
| Max Resolution                     | 4 MP   |                     |
| Sensor                             | 1/1.8" CMOS  |                     |
| Min. Illumination                  | Color: 0.0003 Lux (F1.0, AGC ON)   |                     |
| Shutter                            | Auto/Manual, 1 to 1/100000 s   |                     |
| Adjustment Angle                   | Pan: 8° to 360°, Tilt: 0° to 68°, Rotate: 10° to 360°  |                     |
| S/N                                | > 52 dB  |                     |
| WDR                                | 120 dB   |                     |
| <b>Lens</b>                        |  |                     |
| Focal Length                       | 2.8 mm   | 4.0 mm              |
| Iris Type                          | Fixed  |                     |
| Iris                               | F1.0   |                     |
| Field of View (H)                  | 124.3°   | 96.1°               |
| Field of View (V)                  | 61.4°  | 52.2°               |
| Field of View (D)                  | 135°   | 113.5°              |
| Lens Type                          | Fixed  |                     |
| <b>DORI</b>                        |  |                     |
| DORI Distance (Lens)               | 2.8 mm   | 4 mm                |
| DORI Distance (Detect)             | 43.4 m (142.4 ft.)   | 62.1 m (203.7 ft.)  |
| DORI Distance (Observe)            | 17.4 m (57.1 ft.)  | 24.8 m (81.4 ft.)   |
| DORI Distance (Recognize)          | 8.7 m (28.5 ft.)   | 12.4 m (40.7 ft.)   |
| DORI Distance (Identify)           | 4.3 m (14.1 ft.)   | 6.2 m (20.3 ft.)    |
| <b>Illuminator</b>                 |  |                     |
| Supplemental Light                 | Warm light   |                     |
| Illumination Distance (Warm Light) | 30 m (98.4 ft.)  |                     |
| Light On/Off Control               | Auto/Manual  |                     |
| <b>Video</b>                       |  |                     |
| Video Compression                  | Ultra 265, H.265, H.264, MJPEG   |                     |
| H.264 Code Profile                 | Baseline profile, Main profile, High profile   |                     |
| Frame Rate                         | Main Stream: 4 MP (2688 × 1520), max. 25 fps; 4 MP (2560 × 1440), max. 25 fps; 3 MP (2304 × 1296), max. 30 fps; 1080P (1920 × 1080), max. 30 fps; 720P (1280 × 720), max. 30 fps;<br>Sub Stream: 720P (1280 × 720), max. 30 fps; D1 (720 × 576), max. 30 fps; 640 × 360, max. 30 fps; 2CIF (704 × 288), max. 30 fps; CIF (352 × 288), max. 30 fps; |                     |
| Video Bit Rate                     | 128 Kbps to 6144 Kbps  |                     |
| U-code                             | Support  |                     |
| OSD                                | Up to 4 OSDs   |                     |
| Privacy Mask                       | Up to 4 areas  |                     |
| ROI                                | Support  |                     |
| Video Stream                       | Dual streams   |                     |







| Image                             |  |
|-----------------------------------|--|
| White Balance                     | Auto, Outdoor, Fine tune, Sodium lamp, Locked, Auto2   |
| Digital Noise Reduction           | 2D/3D DNR  |
| Smart Illumination                | Support  |
| Flip                              | Normal, Flip vertical, Flip horizontal, 180°, 90° Clockwise, 90° Anti-clockwise  |
| Dewarping                         | N/A  |
| HLC                               | Support  |
| BLC                               | Support  |
| Defog                             | Digital defog  |
| Events                            |  |
| Basic Detection                   | Motion detection, Ultra motion detection (based on human body and vehicle detection), Tampering alarm, Audio detection   |
| General Function                  | Watermark, IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication  |
| Intelligent                       |  |
| Smart Intrusion Prevention (Lite) | Intrusion, crossline detection (both detection are based on human body and vehicle detection)  |
| Audio                             |  |
| Audio Compression                 | G.711U, G.711A   |
| Audio Bitrate                     | 64 Kbps  |
| Two-way Audio                     | N/A  |
| Suppression                       | Support  |
| Sampling Rate                     | 8 kHz  |
| Storage                           |  |
| Edge Storage                      | MicroSD, up to 512 GB  |
| Network Storage                   | ANR, NAS (NFS)   |
| Network                           |  |
| Protocols                         | IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTSP, DNS, DDNS, NTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, SSL/TLS  |
| Compatible Integration            | ONVIF (Profile S, Profile G, Profile T), API, SDK  |
| User/Host                         | Up to 32 users. 2 user levels: administrator and common user   |
| Security                          | Password Protection, Strong Password, HTTPS Encryption, Export Operation Logs, Basic and Digest Authentication for RTSP, Digest Authentication for HTTP, TLS 1.2, WSSE and Digest Authentication for ONVIF |
| Client                            | EZStation, APP   |
| Web Browser                       | Plug-in required live view: IE 10+, Chrome 45+, Firefox 52+, Edge 79+, Plug-in free live view: Chrome 57+, Firefox 58+, Edge 16+   |
| Interface                         |  |
| Audio I/O                         | N/A  |
| Alarm I/O                         | N/A  |
| Serial Port                       | N/A  |
| Built-in Mic                      | Support  |
| Built-in Speaker                  | N/A  |


|                      |  |
|----------------------|--|
| WIFI                 | N/A  |
| Network              | 1 × RJ45 10 M/100 M Base-TX Ethernet   |
| Video Output         | N/A  |
| <b>Certification</b> |  |
| EMC                  | CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 50130-4)<br>FCC (FCC 47 CFR part15 B)   |
| Safety               | CE LVD (EN 62368-1)<br>UL/CUL (UL 62368-1, CAN/CSA C22.2 No. 62368-1)  |
| Environment          | CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU);  |
| Protection           | IP67 (IEC 60529)<br>IK10 (IEC 62262)   |
| <b>General</b>       |  |
| Power                | DC 12 V±25%, PoE (IEEE 802.3af)  |
| Power Consumption    | Max. 4.0 W   |
| Power Interface      | Ø5.5 mm coaxial power plug   |
| Dimensions           | Ø128 mm × 100 mm (Ø5.0" × 3.9") (Ø × H)  |
| Weight               | 0.53 kg (1.16 lb.)   |
| Material             | Metal + Plastic  |
| Working Environment  | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)  |
| Storage Environment  | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)  |
| Surge Protection     | 4 KV   |
| Reset Button         | Support  |
| Web Client Language  | 13 Languages: English, Simplified Chinese, Polish, German, Russian, French, Korean, Dutch, Czech, Portuguese, Spanish, Spanish (Europe), Italian |

## Dimensions



## Accessories

|  |   |   |
|--|---|---|
| <p><b>TR-JB03-H-IN-V2</b><br/>Junction Box for Metal Turret Camera(Support wiring from behind)</p> | <p><b>TR-CM24-IN</b><br/>Dome Pendant Mounting Bracket(Indoor)</p>                  | <p><b>TR-SE24-A-IN</b><br/>Dome Pendant Mounting Pole 500mm</p>                       |
|                 |  |  |
| <p><b>TR-SE24-IN</b><br/>Dome Pendant Mounting Pole 200mm</p>                                      | <p><b>TR-A01-IN</b><br/>NPT 3/4" Waterproof Cable Gland</p>                         | <p><b>TR-UC08-C-V2</b><br/>Bullet&amp;Dome Corner Mounting Bracket</p>                |
|                 |  |  |

| <p><b>TR-JB07/WM03-F-IN-V2</b><br/>Wall Mounting Assembling Bracket with<br/>Back Hole for 3 Inch Hemisphere</p> | <p><b>TR-WM03-B-IN-V2</b><br/>Wall Mounting Assembling Bracket for 3<br/>Inch Hemisphere</p> | <p><b>TR-UP06-C-IN-V2</b><br/>Pole Mounting Bracket for Bullet Junction<br/>Box Only</p> |
|--|--|--|
|                                 |             |       |
| <p><b>HS-207S</b><br/>Sunshade Shell for Zoom Dome</p>   |  |  |
|                                 |  |  |

# Unlimited New View

## Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



[overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.