

NSW2010-18GT2GP-POE-IN Gigabit Ethernet Switches Datasheet



Features

- Support IEEE802.3 at standard, compatible with IEEE802.3 af by electrical equipment (PD)
- Supports PoE Power up to 30W for each PoE port;
- Auto detect power device; will not burned non-standard PoE device or normal PoE switch;
- Supports port power supply prioritization, guarantee the continuous power supply of key nodes;
- Supports IEEE802.3 x full duplex flow control and Backpressure half duplex flow control;
- Line-speed forwarding, intelligent identification
- Supports storage – and- forward for Data exchange;

Specifications

Model	NSW2010-18GT2GP-POE-IN
Hardware Specification	

Ports Type	16×1000Mbps PoE ports (RJ45)+2×1000Mbps ports(RJ45)+2×1000Mbps ports (SFP)
Standards	IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at
Switching capacity	40 Gbps
MAC	8K
Packet Buffer	4 M bit
Forwarding performance	29.76Mpps
Power supply	AC: 100-240 V, 50/60 Hz
PoE	support POE
Max. PoE Power	Max capacity: 185 W, Max capacity for single port: 30 W
Cooling Fans	1
Weight	<4.2 kg
Indicator	PWR (Green), LNK/ACT (Green), PoE (Orange)
Storage Temperature	-40 °C to 70 °C
Operating temperature	0 °C to 40 °C (32 °F to 104 °F)
Operating humidity	10%~90% (non-condensing)
Storage humidity	5%~90% (non-condensing)
Dimensions (W×D×H)	280mm x 180mm x 44mm (11"×7.1"×1.7")
Working Mode	Default (Normal mode) : All ports can communicate with each other, VLAN (Secure mode): Downlink ports can communicate only with uplink ports., Extend (Surveillance mode): Transmission distance up to 250 meters. Downlink ports can communicate only with uplink ports

Ordering Info

Product Model	Description
NSW2010-18GT2GP-POE-IN	Ethernet Switch(POE)

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China (Zhejiang) Pilot Free Trade Zone, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.