



U3000 series SSD

SSD-1024G-P3-M2



Overview

U3000 series SSD is an M.2 2280 SSD that features small size, low heat generation, and low power consumption. It has four P Cle Gen3 interfaces, provides up to 3000MB/s sequential read speed and 2600MB/s sequential write speed, which is faster and more efficient than traditional HDD and SATA SSD products.

Specifications

Hardware Parameters	Description
TBW Total Byte Written	512TB
Storage particles	TLC
Capacity	1024GB
Max Sequential Read	3000MB/s
Max Sequential Write	2600MB/s

UNV

Max Random Read(4KB)	222K IOPS
Max Random Write(4KB)	164K IOPS
Hardware specification	Description
Interface	PCle 3.0 *4

Ordering Info

Product Model	Description
SSD-1024G-P3-M2	1TByte,PCIe3.0,NVME SSD,UNV

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China (Zhejiang) Pilot Free Trade Zone, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

http://www.uniview.com

©2023-2024 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such

errors and reserves the right to change the contents of this document without prior notice.