


## Wall Plug-in US Power Adapter

### PWR-DC1201A-US



## Specifications

| Model                 | PWR-DC1201A-US                                       |
|-----------------------|------------------------------------------------------|
| Power                 |                                                      |
| Model                 | PWR-DC1201A-US                                       |
| Input                 | AC 100-240V, 50/60Hz, max. 0.4A                      |
| Output                | DC 12V/1.0A                                          |
| Output cable          | DC5521, 1.2m                                         |
| Certification         | ETL, FCC, DOE VI                                     |
| Operating environment | 0°C to 40°C (32°F to 104°F), ≤90%RH (non-condensing) |
| Installation method   | Wall plug-in                                         |

## Ordering Info

| Product Model  | Description                                        |
|----------------|----------------------------------------------------|
| PWR-DC1201A-US | DC12V/1A Wall Plug American Standard Power Adapter |

### Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



[overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China  
(Zhejiang) Pilot Free Trade Zone, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

\*Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.