

3MP LPR Bullet Camera (2.8 to 12mm, PoE, H.265, warm light(IR)) PKC2630@Z28(-IR)-P



Features

- Features
- Optics
 - Built-in lens supports motorized zoom to adapt to different scenes and allows for easy installation.
 - Automatic gain control, white balance, and WDR for various light conditions.
- Compression
 - Supports triple streams.
 - Advanced H.265 encoding technology improves compression efficiency.
 - Custom OSD allows various vehicle information to be overlaid on the video image.
- Functions
 - Built-in vehicle and license plate recognition algorithm can recognize standard license plates of multiple countries.
 - Supports capturing vehicle head only.
 - Supports plate allowlist and blocklist configuration.
 - Supports vehicle access control when connected to a barrier.
 - Supports Micro SD cards of up to 256GB.
 - Automatic network replenishment (ANR) allows to automatically store video to SD card in case of network disconnection.
 - Supports audio collection and intercom.
- Network
 - Network auto-adaptability ensures smooth live video in relatively bad network conditions such as packet loss.
 - Supports SNMP.

- Supports UNP for NAT traversal between public and private networks.
- Supports integration with the third party via SDK or HTTP.
- Network Security
 - Supports authorized user access by password. Weak password detection and account lock-up when failed login attempts reach the upper limit enhance password security.
 - Supports Web access via HTTPS.
 - RTSP authentication prevents unauthorized video stream requests.
 - IP address filtering prevents illegal access from untrusted IP addresses.
 - Gateway ARP protection prevents MAC address spoofing.
- Structure
 - Supports DC 12V and PoE (802.3at) power supplies.
 - Cast aluminum body offers excellent heat dissipation.
 - 3-axis mounting bracket for various installation scenarios.
 - A junction box on the mounting bracket is convenient for storing tail cables.
 - IP67 and IK10 protection.


Specifications

Model	PKC2630@Z28-P		PKC2630@Z28-IR-P	PKC2630@Z28-P	PKC2630@Z28-IR-P
Camera					
Sensor	1/2.8-inch 3MP CMOS				
Focal length	2.8 to 12mm				
Shutter	Auto/Manual, range: 1/30 to 1/100000s				
Minimum illumination	0.003lux (F1.4)	0.005lux (F1.6)		0.003lux (F1.4)	0.005lux (F1.6)
FOV	Horizontal FOV: 101° to 32.6°,Vertical FOV: 54.2° to 18.6°,Diagonal FOV: 119.5° to 35.7°				
WDR	120 dB				
Image					
Image collection format	2304*1296@30 (default), 2304*1296@25				
Frame rate	30 (default), 25, 22, 20, 18, 16, 15, 12.5, 10, 8, 6, 5, 4, 3, 2, 1				
Video compression	H.264 (default), H.265				
ROI	Supports up to 8 regions				
Video OSD	Supports 8 overlay areas and allows contents including date, time, date&time, zoom ratio, custom contents				
Image OSD	Supports 8 overlay areas and allows contents including time, license plate number, device ID, camera ID, allowlist, image authentication ID, custom contents (3 items), location				
Display Parameters					
Resolution	Main stream: 2304*1296,1080P (default), 720P, D1; Sub stream: 720P (default), D1, 2CIF, CIF; Third stream: D1 (default), 2CIF, CIF				
Smart					
Application scenario	≤ 30km/h for entrances and exits, ≤ 80km/h for regular roads;Supports simultaneous application to road and entry/exit scenes without switching				
Vehicle detection mode	Supports video detection				
License plate number recognition	Supports recognition of license plates with numbers and letters by default				

List configuration	Supports allowlist and blocklist configuration, each list allows 20,000 itemsSupports import, export, add, and delete operations			
Barrier opening policy	Open barrier only for the recognized vehiclesOpen barrier for all vehiclesOpen barrier only for vehicles on the allowlistOpen barrier for vehicles not on the blocklistConfigurable Boolean output ID			
Storage				
Edge storage	Supports ANR with a Micro SD card, up to 256GB			
Structure				
Illumination	Built-in integrated illumination module, including 4 warm light LEDs, 50m illumination distance, automatic on/off control	Built-in integrated illumination module, including 4 IR LEDs, 50m illumination distance, automatic on/off control	Built-in integrated illumination module, including 4 warm light LEDs, 50m illumination distance, automatic on/off control	Built-in integrated illumination module, including 4 IR LEDs, 50m illumination distance, automatic on/off control
Bracket	3-axis mounting bracket			
Junction box	The camera comes with a junction box for storing tail cable			
Interface				
BNC	PAL,NTSC			
Network interface	1×10M/100M RJ45			
Serial port	1 × RS485			
Boolean output	1 relay output, withstand voltage: AC 125V/0.3A, DC 30V/1A			
Boolean input	2 x input, supports level (up to DC 5V) and switch signal			
Audio interface	1 × audio input, 1 × audio output			
Storage interface	1 × Micro SD card slot			
Reset button	Support			
Network				
Protocols	IGMP,ICMP,ARP,TCP,UDP,DHCP,PPPoE,RTSP,DNS,DDNS,NTP,UPnP,HTTP,HTTPS,802.1x,SNMP,QoS,SSL/TLS,IPv4,IPv6,SSH			
Compatible Integration	ONVIF (Profile S, Profile G, Profile T),SDK,API			
General				
Weight	2.1kg			
Ingress protection	IP67, IK10			
Power supply	DC12V + 25% - 10%Max. power consumption: 20WSupports PoE (802.3at, class 4)			
Dimensions (L×W×H)	406mm x 126mm x 130mm			
Operating environment	-40℃ to 60℃, ≤90% RH			
Heater	N/A			
Compliance				
NDAA Compliant	Support			
Certification				
EMC	CE-EMC (EN 55032:2015+A11:2020+A1:2020,EN 61000-3-3:2013+A1:2019+A2:2021,EN IEC 61000-3-2:2019+A1:2021, EN 50130-4:2011+A1:2014)FCC(FCC CFR 47 part15 B,ANSI C63.4 2014)			
Safety	EN IEC 62368-1:2020+A11:2020UL (UL 62368-1, 2nd Ed., Issue Date: 2014-12-01)			

Environment	CE-RoHS (2011/65/EU;(EU)2015/863);WEEE (2012/19/EU)
Protection	IP67(IEC60529:1989+AMD1:1999+AMD2:2013)IK10(IEC 62262:2002+AMD1:2021)

Dimensions



Accessories

TR-UP06-C-IN

Pole Mounting Bracket for Bullet Junction

Box Only



Ordering Info

Product Model	Config	Description
PKC2630	Z28-P	3MP LPR Bullet Camera (2.8 to 12mm, PoE, H.265, warm light)
	Z28-P	3MP LPR Bullet Camera (2.8 to 12mm, PoE, H.265, warm light)
	Z28-IR-P	3MP LPR Bullet Camera (2.8 to 12mm, PoE, H.265, IR)

	Z28-IR-P	3MP LPR Bullet Camera (2.8 to 12mm, PoE, H.265, IR)
--	----------	---

Zhejiang Uniview Technologies Co., Ltd.

-  <http://www.uniview.com>
-  overseasbusiness@uniview.com; globalsupport@uniview.com
-  No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China
(Zhejiang) Pilot Free Trade Zone, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.
*Product specifications and availability are subject to change without notice.
*Despite our best efforts, technical or typographical errors may exist in this document.
Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.