Apartment Door Station

OEU-301S-HMKA-NB



Overview

OEU-301S-HMKA-NB apartment door station is one of the terminal equipment of the digital building intercom system, with functions of video intercom, security alarm, video surveillance, etc., providing a safe and comfortable living environment for residents. It can be widely used in apartment building system.

Features

- Delivered with a recess box for recess mount.
- Built-in heating module supports operation at a very low temperature.
- Metal casing.
- Supports batch configuration.
- Supports call and intercom with the connected indoor stations and Guard Live.
- Supports video monitoring, security alarm, and tamper alarm.
- Built-in IC card reader.

Specifications

Model	OEU-301S-HMKA-NB
Basic Business	
WDR	Support
Protocol	Private protocol

1

DATASHEET

	15 buttons with braille
Button	Buttons layout:
	Row 1: 1/2/3
	Row 2: 4/5/6
	Row 3: 7/8/9
	Row 4: */0/#
	Row 5: Management center/Call/Cancel
Network protocol	TCP/IP, IPv4, HTTP, RTP, RTSP, NTP
Specification Index	
Card Capacity	10000
Maximum Connected Indoor Station	500
Hardware Specification	
	Horizontal: 106.9°
	Vertical: 56.9°
FOV	Diagonal: 127.9°
	PoE: 10.73W
	DC12V: 8.62W
Power Consumption	
Volume Adjustment	Support
Audio Quality	Noise suppression, echo cancellation, AGC
Audio Input	1 x Built-in omnidirectional microphone
Audio Output	1 x Built-in speaker
Audio Compression Bitrate	128Kbps
	IP65 (Apply waterproof glue to the gap between the device and the wall. See the
Protection Level	corresponding quick guide for details)
Protection Level	IK08
Power Supply	DC12V ±25%, IEEE802.3af PoE power supply
Operating System	Linux
Illuminator	IR light (adaptive)
Screen Size	3.97 inch
Weight	2.10kg
Mount Method	Wall mount
Network	100Mbps network port, supports IEEE802.3af PoE power supply
Interface	Power*1, network port*1, RS485*1, IO input*4, IO output*2, door lock*2
	(electric lock/door magnet), door opening button*2, door magnet*2, tamper
	button*1
Dimensions (L x W x H)	125mm*358mm*53mm
Operating Environment	-40°C to 60°C, 10% to 90%, noncondensing, outdoor

Ordering Info

Product Model	Description
OEU-301S-HMKA-NB	Apartment Door Station(IC Card,15 Keypads)


Accessories

EP-CS301

301 Door Stations Wall Mounted Sunshade(Metal)



Dimensions



DATASHEET