


## 2MP ColorHunter Fixed Warm Light Turret Analog Camera UAC-T112-F28 (40) -W-X



## Overview

UAC-T112-F28/F40-W-X is a 2MP ColourHunter HD Fixed Turret Analog Camera with a high-performance 1/3-inch CMOS sensor. It supports TVI/AHD/CVI/CVBS, which effectively enhances product adaptability and diversity of networking solutions. With SYV-75-3 or other coaxial cable types the camera can achieve low-cost, long-distance, anti-interference, and low delay mega-pixel HD video transmission. The camera supports 24/7 full-color imaging.

## Features




- 2MP high quality image
- TVI/AHD/CVI/CVBS
- Supports white light illumination, 24/7 full-color imaging
- Supports 180° horizontal flip, 180° vertical flip
- OSD configuration menu, easy to operate
- IP67 waterproof and dustproof design, high reliability
- OSD configuration menu in 11 languages
- 3D noise reduction technology delivers clean and sharp images
- 3-Axis

## Specifications

| Model                   | UAC-T112-F28-W-X                                                                                                                                                                                     |        | UAC-T112-F40-W-X |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|------------------|
| Camera                  |                                                                                                                                                                                                      |        |                  |
| Max Resolution          | 2 MP                                                                                                                                                                                                 |        |                  |
| Sensor Size             | 1/3.0" CMOS                                                                                                                                                                                          |        |                  |
| Min. Illumination       | 0.01 lux (F1.6, AGC ON)<br>0 lux (white light on)                                                                                                                                                    |        |                  |
| Lens                    |                                                                                                                                                                                                      |        |                  |
| Focus                   | 2.8 mm                                                                                                                                                                                               | 4.0 mm |                  |
| Lens Mount              | M12                                                                                                                                                                                                  |        |                  |
| Angle of View (H)       | 100.9°                                                                                                                                                                                               | 82.5°  |                  |
| Angle of View (V)       | 56.5°                                                                                                                                                                                                | 42.1°  |                  |
| Angle of View (D)       | 121.8°                                                                                                                                                                                               | 98.6°  |                  |
| Illuminator             |                                                                                                                                                                                                      |        |                  |
| Illuminator Number      | One white-light illuminator                                                                                                                                                                          |        |                  |
| Illumination Distance   | 20m                                                                                                                                                                                                  |        |                  |
| Lifetime                | ≥ 60000 hours                                                                                                                                                                                        |        |                  |
| Video                   |                                                                                                                                                                                                      |        |                  |
| Resolution              | 1080P: 1920(H)×1080(V)<br>720P: 1280(H) ×720(V)                                                                                                                                                      |        |                  |
| Frame Rate              | TVI: 1080P@25fps (default), 1080P@30fps; 720P@25fps, 720P@30fps<br>AHD: 1080P@25fps, 1080P@30fps; 720P@25fps, 720P@30fps<br>CVI: 1080P@25fps, 1080P@30fps; 720P@25fps, 720P@30fps<br>CVBS: PAL, NTSC |        |                  |
| Shutter Time            | PAL: 1/25 s-1/50000 s, NTSC: 1/30 s-1/50000 s                                                                                                                                                        |        |                  |
| Image                   |                                                                                                                                                                                                      |        |                  |
| Exposure Mode           | Four modes: Global (default), BLC, HLC, DWDR                                                                                                                                                         |        |                  |
| Day/Night               | 24/7 color images                                                                                                                                                                                    |        |                  |
| Digital Noise Reduction | 2D/3D                                                                                                                                                                                                |        |                  |
| White Balance           | Two modes: Auto (default), Manual                                                                                                                                                                    |        |                  |
| WDR                     | DWDR                                                                                                                                                                                                 |        |                  |
| Flip                    | Supports 180°horizontal flip, 180°vertical flip                                                                                                                                                      |        |                  |
| Interface               |                                                                                                                                                                                                      |        |                  |
| Power Interface         | 5.5 mm Power Interface                                                                                                                                                                               |        |                  |
| Video Output            | BNC, supports TVI/AHD/CVI/CVBS                                                                                                                                                                       |        |                  |
| Operating Environment   |                                                                                                                                                                                                      |        |                  |
| Temperature             | -30 °C to 60 °C (-22 °F to 140 °F)                                                                                                                                                                   |        |                  |
| Humidity                | ≤ 95% RH (non-condensing)                                                                                                                                                                            |        |                  |
| Surge Protection        | 4 KV for power, 4 KV for video output interfaces                                                                                                                                                     |        |                  |
| General                 |                                                                                                                                                                                                      |        |                  |
| Power                   | DC 12 V±25%                                                                                                                                                                                          |        |                  |
| Power Consumption       | MAX 2.0W                                                                                                                                                                                             |        |                  |

|                   |                                                                                                                                          |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Mount             | Wall Mount, Pole Mount, Corner Mount, Pendant Mount                                                                                      |
| Dimensions        | Φ118mm*96mm (diameter*height)                                                                                                            |
| Material          | Graphene + Plastic                                                                                                                       |
| Weight            | 205g(0.452lb)                                                                                                                            |
| OSD Menu Language | 11 Languages: English, German, Spanish (Latin America), French, Italian, Japanese, Korean, Polish, Portuguese (Brazil), Russian, Turkish |
| Certification     |                                                                                                                                          |
| EMC               | CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035), FCC (FCC 47 CFR part15 B)                                                   |
| Safety            | CE-LVD (EN 62368-1)                                                                                                                      |
| Environment       | CE-RoHS (2011/65/EU; (EU) 2015/863); WEEE (2012/19/EU)                                                                                   |
| Protection        | IP67 (IEC 60529)                                                                                                                         |

## Dimensions



## Accessories

### TR-JB03-I-IN

Junction Box for Plastic Turret  
Camera(Support wiring from behind)



### TR-WM07P-B

Dome Wall Mounting Plastic Bracket



### TR-A01-IN

NPT 3/4" Waterproof Cable Gland



### TR-SE24-A-IN

Dome Pendant Mounting Pole 500mm



### TR-CM24-IN

Dome Pendant Mounting Bracket(Indoor)



### TR-SE24-IN

Dome Pendant Mounting Pole 200mm



### TR-JB07/WM03-G-IN-V2

Wall Mounting Assembling Bracket For 32  
Fix-dome&Mini Fix-dome&Plastic Turret  
Camera



### TR-WM03-D-IN-V2

Wall Mounting Bracket for 32  
Fix-dome&Mini Fix-dome&Plastic Turret  
Camera



### TR-UC08-C-V2

Bullet&Dome Corner Mounting Bracket



### TR-UP06-C-IN-V2

Pole Mounting Bracket for Bullet Junction  
Box Only



### PWR-DC1201A-UK

DC12V/1A Wall Plug British Standard  
Power Adapter



### PWR-DC1201B-UK

UNV DC12V/1A Wall Plug British Standard  
Power Adapter(Colorful Bag)



### PWR-DC1201A-US

DC12V/1A Wall Plug American Standard  
Power Adapter



### PWR-DC1201B-US

UNV DC12V/1A Wall Plug American  
Standard Power Adapter(Colorful Bag)



### PWR-DC1201A-EU

DC12V/1A Wall Plug European Standard  
Power Adapter



PWR-DC1201B-EU

UNV DC12V/1A Wall Plug European  
Standard Power Adapter(Colorful Bag)



PWR-DC1201A-IND

UNV DC12V/1A Wall Plug Indian  
Standard Power Adapter-Colorful Bag



浙江宇视科技有限公司



<http://www.uniview.com>



[overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)



South Tower, Building 10, Wanlun Science Park, 88 Jiangling Road, Hangzhou, P.R.China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

\*Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.