

UTP Patch Cord Datasheet

GC-CAB6-1m-IN



Features

- Bare Copper conductor
- Excellent performance in the Fluke 100-meter channel test.
- Compliant with RoHS 2.0.
- Stable electrical performance, compliant with TIA-568.2-D, ISO/IEC 11801.
- Suitable for 10BASE-T, 100BASE-TX Fast Ethernet, and 1000BASE-T /1000BASE-TX (Gigabit Ethernet).

Specifications




Model	GC-CAB6-1m-IN
Cable	
Product model	U /UTP CAT6 PVC Patch Cord
Test Standard	TIA-568.2-D, ISO/IEC 11801, RoHS 2.0
Conductor	
Material	Bare Copper (99.95%)
Nom.O.D.(mm)	7*0.16mm±0.005mm, 26AWG
Insulation	
Material	HDPE
Diameter	0.80±0.05 mm
Sheath	
Material	PVC
Thickness	0.55 mm±0.05mm
External O.D.	5.5mm±0.3mm
Color	Blue(RAL5015)

Physical	
Length	1m

Ordering Info

Product Model	Description
GC-CAB6-1m-IN	Cat6 Patch Cord,1m,Blue,Overseas Version

Zhejiang Uniview Technologies Co., Ltd.

-  <http://www.uniview.com>
-  overseasbusiness@uniview.com; globalsupport@uniview.com
-  No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.
*Product specifications and availability are subject to change without notice.
*Despite our best efforts, technical or typographical errors may exist in this document.
Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.