


UTP Category 5E Cables (0.50mm)

CAB-LC2100B-IN



Specifications

Model	CAB-LC2100B-IN
Cable	
Product model	CAB-LC2100B-IN
Packing length	305±1 m
Ambient temperature	-20°C~60°C
Rip-cord	Yes
Conductor	
Material	Solid-Bare Copper
AWG	24
Nom.O.D.(mm)	0.5±0.01 mm
DC resistance	≤95 Ω/km
Insulation	
Diameter	0.9±0.05 mm
Material	HDPE
Thickness	0.2±0.02 mm
Color	Blue/White- Blue,Green/White-Green,Orange/White-Orange,Brown/White-Brown
Pitch	
Offset pitch	≤25 mm
Cable pitch	≤140 mm
Sheath	
Material	PVC(complies RoHS/REACH)
Thickness	0.55±0.05 mm

External O.D.	5.1±0.3 mm
Tensile strength	>13.5 Mpa
Color	Gray(RAL7046)
Surface Printing	
Color	Black
Letter height	3.0±0.3 mm
Print error / Space	1±0.005 m
Case number	Yes
Packing	
Packing	Carton
Once packing dimension	350mm*216mm*350mm
Twice packing dimension	370mm*460mm*370mm

Ordering Info

Product Model	Description
CAB-LC2100B-IN	Cat5e(UTP)-305m-Overseas

Unlimited New View

浙江宇视科技有限公司



<http://www.uniview.com>



overseasbusiness@uniview.com; globalsupport@uniview.com



South Tower, Building 10, Wanlun Science Park, 88 Jiangling Road, Hangzhou, P.R.China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

虽然我司试图在本资料中提供准确的信息，但不保证资料的内容不含有技术性误差或印刷性错误，为此我司对本资料中的不准确不承担任何责任。我司保留在没有通知或提示的情况下对本资料的内容进行修改的权利。