

## 4MP IR Fixed Bullet Network Camera

IPC-B234-AF40-ECO



## Features

- High quality image with 4 MP, 1/3.0" CMOS sensor
- 4 MP (2560 × 1440)@25/20 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
- Supports accurate human body detection 2.0
- Ultra 265, H.265, H.264
- 2D/3D DNR (digital noise reduction)
- ROI (region of interest) ensures image quality in areas of interest with low bandwidth
- Smart IR, up to 30 m (98.4 ft.) IR distance
- 3-axis
- Built-in mic
- Wide temperature range: -30 °C to 60 °C (-22 °F to 140 °F)
- Supports PoE power supply
- IP67


## Specifications

| Model                      | IPC-B234-AF40-ECO                                                                                                                                                                                                  |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Camera                     |                                                                                                                                                                                                                    |
| Max Resolution             | 4 MP                                                                                                                                                                                                               |
| Sensor                     | 1/3.0" CMOS                                                                                                                                                                                                        |
| Min. Illumination          | Color: 0.01 Lux (F2.0, AGC ON), 0 Lux with IR on                                                                                                                                                                   |
| Day/Night                  | IR-cut filter with auto switch (ICR)                                                                                                                                                                               |
| Shutter                    | Auto/Manual, 1 to 1/100000 s                                                                                                                                                                                       |
| Adjustment Angle           | Pan: 0° to 360°, Tilt: 0° to 90°, Rotate: 0° to 360°                                                                                                                                                               |
| S/N                        | > 52 dB                                                                                                                                                                                                            |
| WDR                        | DWDR                                                                                                                                                                                                               |
| Lens                       |                                                                                                                                                                                                                    |
| Focal Length               | 4.0 mm                                                                                                                                                                                                             |
| Iris                       | F2.0                                                                                                                                                                                                               |
| Field of View (H)          | 74.6 °                                                                                                                                                                                                             |
| Field of View (V)          | 40.5°                                                                                                                                                                                                              |
| Field of View (D)          | 89.1 °                                                                                                                                                                                                             |
| Lens Type                  | Fixed                                                                                                                                                                                                              |
| Iris Type                  | Fixed                                                                                                                                                                                                              |
| DORI                       |                                                                                                                                                                                                                    |
| DORI Distance (Lens)       | 4 mm                                                                                                                                                                                                               |
| DORI Distance (Detect)     | 90.0 m (295.3 ft)                                                                                                                                                                                                  |
| DORI Distance (Observe)    | 36.0 m (118.1 ft.)                                                                                                                                                                                                 |
| DORI Distance (Recognize)  | 18.0 m (59.1 ft.)                                                                                                                                                                                                  |
| DORI Distance (Identify)   | 9.0 m (29.5 ft.)                                                                                                                                                                                                   |
| Illuminator                |                                                                                                                                                                                                                    |
| Supplemental Light         | IR                                                                                                                                                                                                                 |
| Illumination Distance (IR) | 30 m (98.4 ft.)                                                                                                                                                                                                    |
| Wavelength                 | 850 nm                                                                                                                                                                                                             |
| Video                      |                                                                                                                                                                                                                    |
| Video Compression          | Ultra 265, H.265, H.264                                                                                                                                                                                            |
| H.264 Code Profile         | Baseline profile, Main profile, High profile                                                                                                                                                                       |
| Frame Rate                 | Main Stream: 4 MP (2560 × 1440), max. 25 fps; 3 MP (2304 × 1296), max. 30 fps; 1080P (1920 × 1080), max. 30 fps<br>Sub Stream: 640 × 360, max. 30 fps; 2CIF (704 × 288), max. 30 fps; CIF (352 × 288), max. 30 fps |
| Video Bit Rate             | 128 Kbps to 6144 Kbps                                                                                                                                                                                              |
| U-code                     | Support                                                                                                                                                                                                            |
| OSD                        | Up to 4 OSDs                                                                                                                                                                                                       |
| Privacy Mask               | Up to 4 areas                                                                                                                                                                                                      |
| ROI                        | Support                                                                                                                                                                                                            |
| Video Stream               | Dual streams                                                                                                                                                                                                       |

| Image                   |                                                                                                                                                                                 |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Smart Illumination      | Support                                                                                                                                                                         |
| White Balance           | Auto, Outdoor, Fine tune, Sodium lamp, Locked, Auto2, Area white balance                                                                                                        |
| Digital Noise Reduction | 2D/3D DNR                                                                                                                                                                       |
| Smart IR                | Support                                                                                                                                                                         |
| Flip                    | Normal, Flip vertical, Flip horizontal, 180°                                                                                                                                    |
| Dewarping               | N/A                                                                                                                                                                             |
| HLC                     | Support                                                                                                                                                                         |
| BLC                     | Support                                                                                                                                                                         |
| Defog                   | Digital defog                                                                                                                                                                   |
| Image Stabilization     | N/A                                                                                                                                                                             |
| Events                  |                                                                                                                                                                                 |
| Basic Detection         | Motion detection, Audio detection, Human body detection 2.0                                                                                                                     |
| General Function        | Watermark, IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication                                                   |
| Audio                   |                                                                                                                                                                                 |
| Audio Compression       | G.711U, G.711A                                                                                                                                                                  |
| Audio Bitrate           | 64 Kbps                                                                                                                                                                         |
| Two-way Audio           | N/A                                                                                                                                                                             |
| Suppression             | Support                                                                                                                                                                         |
| Sampling Rate           | 8 kHz                                                                                                                                                                           |
| Storage                 |                                                                                                                                                                                 |
| Edge Storage            | N/A                                                                                                                                                                             |
| Network                 |                                                                                                                                                                                 |
| Protocols               | IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, UPnP, HTTP, HTTPS, SNMP, QoS, SSL/TLS                                                             |
| Compatible Integration  | API, SDK                                                                                                                                                                        |
| Client                  | APP, Uniarch client                                                                                                                                                             |
| Web Browser             | Plug-in required live view: IE 10+, Chrome 45+, Firefox 52+, Edge 79+, Plug-in free live view: Chrome 57+, Firefox 58+, Edge 16+                                                |
| Security                | Password Protection, Strong Password, Export Operation Logs, Basic and Digest Authentication for RTSP, Digest Authentication for HTTP, WSSE and Digest Authentication for ONVIF |
| User/Host               | Up to 32 users. 3 user levels: administrator, common user and operator                                                                                                          |
| Interface               |                                                                                                                                                                                 |
| Audio I/O               | N/A                                                                                                                                                                             |
| Alarm I/O               | N/A                                                                                                                                                                             |
| Serial Port             | N/A                                                                                                                                                                             |
| Built-in Mic            | Support                                                                                                                                                                         |
| Built-in Speaker        | N/A                                                                                                                                                                             |
| WIFI                    | N/A                                                                                                                                                                             |
| Network                 | 1 × RJ45 10 M/100 M Base-TX Ethernet                                                                                                                                            |
| Video Output            | N/A                                                                                                                                                                             |
| Certification           |                                                                                                                                                                                 |

|                     |                                                                                                    |
|---------------------|----------------------------------------------------------------------------------------------------|
| Protection          | IP67 (IEC 60529)                                                                                   |
| EMC                 | CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 50130-4)<br>FCC (FCC 47 CFR part15 B)         |
| Safety              | CE LVD (EN 62368-1)                                                                                |
| Environment         | CE-RoHS (2011/65/EU;(EU)2015/863)<br>WEEE (2012/19/EU)<br>Packaging and Packaging Waste (94/62/EC) |
| General             |                                                                                                    |
| Power               | PoE (IEEE 802.3af)                                                                                 |
| Power Consumption   | Max. 3.1 W                                                                                         |
| Power Interface     | N/A                                                                                                |
| Dimensions          | 196.5 mm × 73.0 mm × 72.9 mm (7.7" × 2.9" × 2.9") (L × W × H)                                      |
| Weight              | 0.22 kg (0.49 lb.)                                                                                 |
| Material            | Graphene + Plastic                                                                                 |
| Working Environment | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)                            |
| Storage Environment | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)                            |
| Surge Protection    | 4 KV                                                                                               |
| Reset Button        | N/A                                                                                                |
| Web Client Language | 4 Languages: English, Russian, Spanish, Vietnamese                                                 |

## Dimensions



## Accessories

| TR-JB05-A-IN                                                                        | TR-UP06-B-IN                                                                        | TR-A01-IN                                                                             |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Small Bullet Junction Box(Support wiring from behind,Square)                        | Bullet Pole Mounting Bracket                                                        | NPT 3/4" Waterproof Cable Gland                                                       |
|  |  |  |
| TR-UP06-C-IN-V2                                                                     | TR-UC08-C-V2                                                                        |                                                                                       |
| Pole Mounting Bracket for Bullet Junction Box Only                                  | Bullet&Dome Corner Mounting Bracket                                                 |                                                                                       |
|  |  |                                                                                       |

**Zhejiang Uniview Technologies Co., Ltd.**<http://www.uniview.com>[overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

\*Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.