

# UTP Category 6 CCA Cables (0.56mm)

CAB-LC3100B-CCA-IN



## Specifications

Model	CAB-LC3100B-CCA-IN
Cable	
Product model	CAB-LC3100B-CCA-IN
Test Standard	Fluke Test 90m
Packing length	305±1 m
Rip-cord	Yes
Seperator	Yes
Ambient temperature	-20°C~75°C
Conductor	
Material	CCA (23%)
AWG	23

Nom.O.D.(mm)	0.56±0.01 mm
<b>Insulation</b>	
Material	HDPE
Diameter	1.03±0.03 mm
Color	Blue/White- Blue,Green/White-Green,Orange/White-Orange,Brown/White-Brown
<b>Sheath</b>	
Material	PVC
External O.D.	6.0±0.4 mm
Thickness	0.5±0.05 mm
Color	White
<b>Surface Printing</b>	
Letter height	3.0±0.3 mm
Print error / Space	1±0.005 m
Color	Black
<b>Packing</b>	
Packing	Pallet
Once packing dimension	420mm*205mm*420mm

## Ordering Info

Product Model	Description
CAB-LC3100B-CCA-IN	Cat6(UTP),305m,CCA,White

### Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China (Zhejiang) Pilot Free Trade Zone, China

Email: [overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)

<http://www.uniview.com>

©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

\*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.