

Core Switch

IN9800-A3-IN



Overview

With the wide application of new technologies such as cloud computing and Web2.0, the network data transmission capacity has grown exponentially. According to Gilder's law, the bandwidth will double every six months in the next 25 years. Such rapidly growing data services will not only make the network architecture very complex, but also face enormous challenges such as network security, application experience, and continuous service availability. IN9800 Series adopts the CLOS multi-level switching architecture, the control plane and the forwarding plane are physically separated, and the main control engine and the switch fabric board hardware is independent of each other. The product is designed based on the 100G platform, which meets the expansion requirements of high-density 40G and 100G interfaces, supports a variety of data center features, and realizes the deep integration of network and business, providing enterprises with a high-speed, intelligent and reliable next-generation network infrastructure platform. IN9800 Series adopts a number of innovative cooling technologies such as dual air duct design, which can reduce equipment power consumption and environmental noise, and save energy and protect the environment. The redundant design of its key components provides multiple technologies such as uninterrupted restart, hot patching, ring network protection, and separation of data/control/monitoring planes to ensure 99.999% carrier-grade reliability.

Features

- Strong service processing capabilities. It supports perfect Layer 2 and 3 multicast protocols such as PIM SM, PIM DM, PIM SSM, MLD, and IGMP Snooping, and meets the requirements of multi-terminal HD video surveillance and video conferencing access.
- Complete security control policies. IN9800 Series supports MAC address authentication, 802.1x authentication, and PORTAL authentication, and has a built-in authentication server. It supports dynamic or static binding of user identity elements such as user accounts, IPs, MACs, VLANs, and ports, and implements dynamic delivery of user policies.
- Virtualization features. Relying on the self-developed VSM technologies, IN9800 Series can transform multiple similar service modules into "resource pools" that can be flexibly scheduled, realize the "granularization" of service platform resources, and greatly improve the resource utilization efficiency.
- Comprehensive IPV4/IPV6 dual stack. IN9800 Series hardware supports IPV4/IPV6 dual-stack and IPV6 over IPV4 tunnels (including

manual tunnels, 6to4 tunnels, and ISATAP tunnels), and supports IPv6 Layer 3 line-speed forwarding, which can be used for pure IPv4 or IPv6 networks, as well as IPv4 to IPv6 coexistence networks.

- Carrier-grade high reliability. IN9800 Series supports technologies such as master control redundancy, fan redundancy, N+1 power supply, uninterrupted reboot, hot patching, and data/control/monitoring plane separation to ensure 99.999% carrier-class reliability. Fast fault detection technologies such as BFD and OAM provide a variety of device-level and network-level fault detection methods.
- Environment-friendly and energy-saving. IN9800 Series adopts a number of innovative heat dissipation technologies such as dual air duct design, and the heat dissipation efficiency is increased by 30%.

Specifications

Model	IN9800-A3-IN
Hardware Specification	
MPU Slots	2*Half-width slot
SFU Slots	0
Module Slots	3
Switching capacity	1.44Tbps
Forwarding performance	857.08Mpps
Fan Slots	1
Cooling Fans	4
Air Inlet and outlet direction	Right-side inlet, backend outlet
Power Slots	2, 1 to 2 service boards, recommend 1 power supply; 3 service boards, recommend 2 power supply.
Power Supply	110V AC to 240V AC, 50/60Hz
Max.Power	550W
Dimensions (W×D×H)	420*480 *175mm, 4U
Operating Temperature	0°C to 45°C
Operating Humidity	5% to 95%, non-condensing
MTBF	>200000h
Weight	Empty Frame: ≤13.5kg Fully Loaded: ≤30kg
Software Specification	
Layer-2	VLAN, STP, RSTP, MSTP, QinQ, flexible QinQ, VLAN Mapping, full duplex traffic control, back pressure traffic control, link aggregation (support 128 aggregation groups, with each group consisting of 8 members), cross-board link aggregation, cross-board port/flow mirroring, port broadcast/multicast/unknown unicast forwarding storm suppression, Jumbo Frame, VLAN division based on port/protocol/subnet and MAC, PVLAN, GVRP, CoS priority, etc.
Layer-3	IPv4: Static routing, RIP v1/2, OSPF, ISIS, BGP, policy-go-together, etc. IPv6: IPv6 static routing, RIPng, OSPFv3, ISISv6, BGP4+, transition tunnel technology from IPv4 to IPv6, etc.
Data Center	Support 802.1Qbg and DCB Support mainstream Overlay standards such as VXLAN Support Openflow1.3 protocol

Virtualization	<p>Support VSM (Virtual Switching Matrix) N:1 virtualization technology, which performs virtualization of multiple L2 ~ 7 physical devices into a single L2 ~7 logical device.</p> <p>Support service chain technology, which defines business streams based on L2-7 protocol features, and allows on-demand assignment of physical/logical service modules for traffic passage.</p> <p>Support IP-based unified management between the host and service modules and unified configuration interface</p>
Reliability	<p>Support master control board 1+1 redundancy</p> <p>Support power N+1 redundancy</p> <p>Passive backplane design; all boards support hot-plug</p> <p>Support online status monitoring protocol to perform detection of key components including master control engine, backplane, chip and storage</p>
Multicast	Support IGMPv1/v2/v3, IGMPv1/v2/v3 Snooping, PIM-SM/PIM-DM/PIM-SSM
ACL	Support ACL rules including source IP, source port, destination IP, destination port, protocol number, physical port
Maintenance	<p>Support FTP, TFTP, X-modem</p> <p>Support Web management port, SNMP v1/v2/v3</p> <p>Support RMON, NTP clock, intelligent power management</p>

Selection Info

FB-IN9800-MPU-A3	UNV,FB-IN9800-MPU-A3-IN,A3 Main Control Module
FB-IN9800-48GT	UNV,FB-IN9800-48GT-IN,48 Gigabit Power Ethernet Interface Module
FB-IN9800-48GP	UNV,FB-IN9800-48GP-IN,48 Gigabit Optical Ethernet Interface Module
FB-IN9800-24GT20GP4XP	UNV,FB-IN9800-24GT20GP4XP-IN,24 Gigabit Power 20 Gigabit Optical 4 10 Gigabit Optical Ethernet Interface Module
FB-IN9800-8XP	UNV,FB-IN9800-8XP-IN,8 10 Gigabit Optical Ethernet Interface Module
FB-IN9800-24XP-IN	UNV,FB-IN9800-24XP-IN,Ethernet Interface Module(24SFP+)
FB-IN9800-48XP	UNV,FB-IN9800-48XP-IN,48 10 Gigabit Optical Ethernet Interface Module
FB-IN9800-6QP-IN	UNV,FB-IN9800-6QP-IN,Ethernet Interface Module(6 QSFP+)
PWR-IN9800-AC550-A3A6	UNV,PWR-IN9800-AC550-A3A6-IN,Alternating A3A6 Power Adapter

Ordering Info

Product Model	Description
IN9800-A3-IN	IN9800 A3 Intelligent Switch Gateway

Unlimited New View

Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



overseasbusiness@uniview.com; globalsupport@uniview.com



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.