

## Managed Industrial PoE Switch

# IS5000-4GT4GP-POE-IN@PWR75



## Features

- Support IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3z /ab, IEEE802.1Q, IEEE802.1p, IEEE802.1d/w
- Support PoE power management and PoE Watchdog based on data flow detection
- Support IEEE802.3af (15.4W) and IEEE802.3at (30W)
- Support SNMP v1/v2/v3 Simple Network Management Protocol
- Support IGMP Snooping, static multicast filtering, and MLD Snooping filtering
- Support 802.1x port authentication and AAA authentication to enhance network security
- Support WEB, Telnet, CLI, SSH management
- IP40 protection level, high-strength shell, DIN35 rail installation
- Industrial grade 4-level design, operating temperature from -40~75°C
- Support redundant power supply connection and anti reverse connection;


## Specifications

| Model                  | IS5000-4GT4GP-POE-IN@PWR75                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hardware Specification |                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Standards              | IEEE802.3 (Ethernet)<br>IEEE802.3u (Fast Ethernet)<br>IEEE 802.3ab (Gigabit Ethernet)<br>IEEE 802.3z (Gigabit Ethernet Fiber Standard)<br>IEEE802.3x (Flow Control)<br>IEEE 802.1D Spanning Tree Protocol<br>IEEE 802.1w Rapid Spanning Tree Protocol                                                                                                                                                                                 |
| Ports Type             | 4*10/1000Mbps RJ45 PoE Ports<br>4*1000Mbps SFP Slots<br>1*Console port                                                                                                                                                                                                                                                                                                                                                                |
| Switching capacity     | 16Gbps                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Forwarding performance | 8.92Mpps                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Packet Buffer          | 4 M bit                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Max.PoE Power          | Max capacity: 65W<br>Max capacity for single port: 30W<br>Mode A 1/2 (-), 3/6 (+)                                                                                                                                                                                                                                                                                                                                                     |
| Max.Power              | 75W                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| MAC                    | 8K                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Transfer Mode          | Store-and-forward                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Dimensions (W×D×H)     | 164*107*51mm                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Operating Temperature  | -40°C to 75 °C                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Operating Humidity     | 10% ~ 95% non-condensing                                                                                                                                                                                                                                                                                                                                                                                                              |
| Storage Humidity       | 5% ~ 95% non-condensing                                                                                                                                                                                                                                                                                                                                                                                                               |
| Indicator              | PWR (Green)<br>Off: Powered off<br>On: Powered on<br>SYS(Green)<br>Flashing: System startup in progress<br>On: System startup completed<br>Ports 1-4/Ports1-8 (Green)<br>Slow Flashing: 10/100/1000Mbps Link normal<br>Off: Link blocked<br>Fast Flashing: Data transmitting<br>Ports 1-4(Yellow)<br>On: PoE powered on<br>Off: PoE powered off<br>Ports G5-G8/G9-G12 (Green)<br>On: 10/100/1000Mbps Link normal<br>Off: Link blocked |

|                        |                                                                                                                                                                                                                                                                                                   |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                        | Flashing: Data transmitting                                                                                                                                                                                                                                                                       |
| Electrostatic Standard | Air 8KV, Contact 6KV (Class B)                                                                                                                                                                                                                                                                    |
| Surge Protection       | Common mode 6KV, Differential mode 2KV (Class B)                                                                                                                                                                                                                                                  |
| Power Supply           | DC:48-57V, powered by adapter (NVR-75-48, input voltage : 100-240V AC , output voltage : 48V DC, 1.6A , 32*125.2*113.5mm, DIN35 rail installation)                                                                                                                                                |
| Button                 | Dual color LED selection: default green (link data), switch yellow LED(PoE)<br>Long press for 6 seconds to restore factory settings                                                                                                                                                               |
| Software Specification |                                                                                                                                                                                                                                                                                                   |
| Ethernet               | Port Switch configuration<br>Port Description configuration<br>Port Speed configuration<br>Port Duplex configuration<br>Port Flow Control configuration<br>Jumbo Frame<br>IEEE<br>Fiber Module(DDM)<br>Port Isolation<br>Port Rate-limit<br>Loopback Detection<br>Port Mirroring<br>Storm Control |
| VLAN                   | Access/Trunk/Hybrid<br>VLAN Tunnel (Q-in-Q Tunnel)<br>VLAN range 1-4094, maximum active VLAN is 4K<br>Voice VLAN, MAC VLAN, Surveillance VLAN, Protocol VLAN,<br>GVRP                                                                                                                             |
| MAC                    | Dynamic MAC address<br>Static MAC address<br>Filtering MAC Address                                                                                                                                                                                                                                |
| Reliability            | STP/RSTP/MSTP, BPDU Filter, BPDU Guard, Edge Port, ERPS                                                                                                                                                                                                                                           |
| Multicast              | IGMP Snooping<br>IGMP V1/V2/V3<br>Router Port<br>Static IGMP group address<br>IGMP groups filtering<br>Querier<br>MLD Snooping<br>MVR                                                                                                                                                             |
| POE                    | PoE Temperature<br>PoE Type/Level/Power/Voltage/Current query<br>PoE Switch Configuration<br>PoE Watchdog Configuration<br>PoE power AF/AT adaptation<br>PoE Schedule                                                                                                                             |

|             |                                                                                                                                                                                               |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|             | PoE Port Timer Reboot                                                                                                                                                                         |
| DHCP        | DHCP Server, IP Pool, Static Binding, Option 43, DHCP Relay,DHCP Snooping(Global/VLAN, Option 82, Circuit ID)                                                                                 |
| ACL         | MAC ACL, IPv4 ACL, IPv6 ACL                                                                                                                                                                   |
| IP Route    | IPv4 Static Routes<br>IPv6 Static Routes                                                                                                                                                      |
| Maintenance | Console, HTTP/HTTPS, Telnet, SSH, SNMP<br>Mnager IP(Static Address,DHCP Client,Support IPv4 and IPv6 address,Manager VLAN,DNS)<br>SNMP(V1/V2C/V3,Community,V3 User,Group,Trap Host)<br>Syslog |
| Security    | AAA(RADIUS, TACACS+, 802.1X,Base on port/MAC/local/WEB)                                                                                                                                       |
| QoS         | Traffic classification based, Strict priority and WRR<br>Port Priority<br>802.1P Priority<br>IP TOS Priority<br>IP DSCP Priority<br>Support up to 8 queues per port<br>Priority Remarking     |

# Dimensions



# Unlimited New View

## Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



[overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2026 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.