

EZWall Video Wall Client Software SWP-EZWall



Features

- Supports multiple device models including DC5504/06/10-E-V2,ADU8706/09/12-E-V3,DMC9000-2U-V3 and DMC9000-3U
- Supports Uniview and other manufacturers' IPC and NVR.
- Live view, sequence display, and play signal source on video wall, open windows by one click, split window, window roaming, virtual
- LED, scenes and scene plans.
- Supports small pixel pitch LED, turn on/off Uniview screens automatically at a set time, turn on/off manually or with a delay.

Specifications

Model	SWP-EZWall
BOM	
ВОМ	0501C1KH
Function	
Device Management	Add, edit, and delete devices on LAN
	Supports automatic search, and allows user to add devices manuallyOpen device's Web
	interface from the clientView device status, including status of NVR-connected IPCsSupports
	Onvif

1



Video Wall	Add, edit, and delete video walls; supports small pixel pitch LED Bind decoding channels automatically, bind decoding channels by one-click, splice screens, custom screen layoutScene and scene plan (execute by set time interval or 24-hour schedule)Multiple ways to open windows: one click (1/3/4/5/6/7/8/9/10/13/16/17/25/32/36/64 and M*N custom layout), right mouse button, or coordinatesWindow roaming and overlay, double-click window to view in full screen mode, renumber windows, window lock/unlock, display on top/bottom, and view window/split window infoStart videos in batches on one or multiple screensSequence display videos in one or multiple windowsPlay PC's video signals through server's DVI or VGA interface to the video wallDevice group, including default group and custom groupVirtual LED: LED coordinates, custom LED content, font style, font size, font color, character spacing and alignment, background color and transparency, moving speed and mode; enable/disable virtual LEDsSupports audio output and volume adjustment
Sequence Resource	Add, edit, and delete sequence resource
Screen Control	Turn on/off screen automatically at a set time Turn on/off screen manuallyTurn on/off screen with delay
Client Configuration	Automatic login to EZWall Automatic login to WindowsAutomatically display selected window on topPlay video with set or adaptive stream type
Help	User manual
Language	Chinese、 English
Environment	
OS and Min. Requirements	OS: 32-bit or 64-bit Microsoft Windows 7, 8, 10 CPU: Intel Core i5 2.3GHz or higherRAM: 4GB or higher

Zhejiang Uniview Technologies Co., Ltd.



http://www.uniview.com



overse as business @uniview.com; global support @uniview.com



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China (Zhejiang) Pilot Free Trade Zone, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

^{*}Product specifications and availability are subject to change without notice.

^{*}Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.