


Ethernet PoE Switches Datasheet

NSW2020-6T-POE-IN



Features

- Multiple working modes to address your business needs: Default(Normal mode), EXTEND(Surveillance mode)
- Support port traffic control
- Up to 250m transmission distance on Extend mode
- Support buffer optimization
- All metal housing, safe and reliable

Specifications

| | |
|------------------------|--|
| Model | NSW2020-6T-POE-IN |
| Hardware Specification | |
| Ports Type | 6×100Mbps network ports (RJ45), including 4 PoE ports |
| Standards | IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at |
| Switching capacity | 1.2 Gbps |
| Packet Buffer | 448K bit |
| Forwarding performance | 0.90Mpps |
| MAC | 1K |
| Prior Ports | 1 to 2 |
| Power Supply | DC: 48/51V, powered by adapter (AC100-240V, 50/60Hz) |

| | |
|-----------------------|--|
| PoE | support POE |
| Max. PoE Power | Max capacity: 60 W, Max capacity for single port: 30 W |
| Storage Temperature | -40 °C to 70 °C |
| Operating humidity | 10%~90% (non-condensing) |
| Cooling Fans | 0 |
| Weight | 0.19KG |
| Dimensions (W×D×H) | 107*101*25mm |
| Storage humidity | 5%~90% (non-condensing) |
| Operating temperature | 0 °C to 40 °C (32 °F to 104 °F) |
| Indicator | POWER Steady on: AC input is normal, POWER Off: No AC input, No PoE Indicator, PoE-MAX off: The POE power supply power of the whole machine is less than 80% of the specification, PoE-MAX Steady on : The POE power supply power of the whole machine is greater than 85% of the specification, LINK/ACT Off: No link, LINK/ACT Steady on: Linked, LINK/ACT Flashing: Transmitting data |
| Working Mode | Default (Normal mode) : All ports can communicate with each other, EXTEND (Surveillance mode): Transmission distance up to 250 meters |

Ordering Info

| Product Model | Description |
|-------------------|--------------------------------|
| NSW2020-6T-POE-IN | Unmanaged Ethernet Switch(PoE) |

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.