


UTP Category 5E Cables (0.45mm)

CAB-LC2100A-E2-ECA-IN



Specifications

Model	CAB-LC2100A-E2-ECA-IN
Cable	
Product model	CAB-LC2100A-E2-ECA-IN
Product specification	HSYV-5e 4×2×0.45
Test Standard	Fluke Test 90m
Packing length	305±1 m
Rip-cord	Yes
Ambient temperature	-20°C~75°C
Conductor	
Material	Solid-Bare Copper
AWG	25

Nom.O.D.(mm)	0.45±0.01 mm
DC resistance	≤113 Ω/km
Insulation	
Material	HDPE
Diameter	0.82±0.05 mm
Color	Blue/White- Blue,Green/White-Green,Orange/White-Orange,Brown/White-Brown
Sheath	
Material	PVC
External O.D.	4.7±0.3 mm
Thickness	0.5±0.1 mm
Tensile strength	>13.8 Mpa
Color	Gray
Surface Printing	
Color	Black
Letter height	3.0±0.3 mm
Print error / Space	1±0.005 m
Packing	
Packing	Pallet
Once packing dimension	340mm*220mm*340mm

Ordering Info

Product Model	Description
CAB-LC2100A-E2-ECA-IN	Cat5e(UTP),305m,BC,Gray

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.