Unmanaged Ethernet Switch
NSW1010-8T-IN

Overview

The NSW1010 series unmanaged Ethernet switch is a plug-and-play device with no configuration required. The fanless silent design completely eliminates the loud noise caused by other small switches used in the office. The small size and exquisite appearance save the space effectively. It can be widely used in industries such as network video management, hotels, campuses, small and medium-sized enterprises network, etc.

Features

- Supports IEEE802.3 and IEEE802.3u standards.
- Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port.
- Supports auto MDI/MDIX.
- Supports IEEE802.3 flow control for full-duplex mode and backpressure for half-duplex mode.

Specifications

Model	NSW1010-8T-IN
Hardware Specification	
Ports Type	8 x 10/100Mbps port (RJ45)
Switching capacity	1.6 Gbps
MAC	2K
Forwarding performance	1.19Mpps
Standards	IEEE802.3 IEEE802.3u IEEE802.3x
Power Supply	DC: 5V 1A, powered by adapter (AC: 100 to 240V)

Carton Information	Carton dimensions: 530*475*315mm Carton quantity: 100PCS Carton weight: 17.6kg
Mount Method	Desktop mount, wall mount
Cooling Fans	0
Dimensions (W×D×H)	Product: 145*60*21.5mm Packaging: 146*88*50mm
Operating Temperature	-10 to 50 C (14 F to 122 F)
Operating Humidity	10% to 90% (noncondensing)
Indicator	POWER: Steady on: AC input is normal Off: No AC input LINK/ACT： Off: No link Steady on: Linked Flashing: Transmitting data
Weight	Product: 0.111kg Packaging: 0.166kg