# Villa Door Station

#### OEU-202S-HMK2-NB



#### Overview

OEU-202S-HMK2-NB villa door station is one of the terminal equipment of the digital building intercom system, with functions of video intercom, security alarm, video surveillance, etc., providing a safe and comfortable living environment for residents. It can be widely used in villa building system.

#### Features

- Optional recess box for recess mount.
- Supports power output, which can be enabled or disabled on the Web interface.
- Built-in heating module supports operation at a very low temperature.
- Metal casing.
- Supports batch configuration.
- Supports call and intercom with the connected indoor stations and Guard Live .
- Supports video monitoring, security alarm, and tamper alarm.
- Built-in IC card reader.

### Specifications

Model	OEU-202S-HMK2-NB	
Basic Business		
WDR	Support	
Protocol	Private protocol	
Button	2 x Call button	
Network protocol	TCP/IP, IPv4, HTTP, RTP, RTSP, NTP	

## DATASHEET

_			
Spe	citic	ation	Index

Specification Index	Specification Index			
Card Capacity	10000			
Maximum Connected Indoor Station	20			
Hardware Specification				
	Horizontal: 106.9°			
FOV	Vertical: 56.9°			
	Diagonal: 127.9°			
	PoE: 6.48W			
Power Consumption	DC12V: 5.35W			
Volume Adjustment	Support			
Audio Quality	Noise suppression, echo cancellation, AGC			
Audio Input	1 x Built-in omnidirectional microphone			
Audio Output	1 x Built-in speaker			
Audio Compression Bitrate	128Kbps			
	IP65 (Apply waterproof glue to the gap between the device and the wall. See the			
Protection Level	corresponding quick guide for details)			
	IK08			
Power Supply	DC12V ±25%, IEEE802.3af PoE power supply			
Operating System	Linux			
Illuminator	IR light (adaptive)			
Weight	675g			
Mount Method	Wall mount			
Network	100Mbps network port, supports IEEE802.3af PoE power supply			
Interface	Power*1, network port*1, RS485*1, Wiegand*1, IO input*4, door lock*2 (support			
	electric lock/door magnet), tamper button*1			
Dimensions (L x W x H)	96mm*176mm*33mm			
Operating Environment	-40°C to 60°C, 10% to 90%, noncondensing, outdoor			

## Ordering Info

Product Model	Description
OEU-202S-HMK2-NB	Villa Door Station(IC Card,2 Keypads)



### Accessories

EP-SZ202

EP-CS202

202 Door Stations Sunshade(Metal)

202 Door Stations Embedded Bracket(Plastic)





### Dimensions

