

Ethernet Switch Datasheet

NSW5110-24GT4GP-IN



Features

- Support RJ45 Auto-MDI/MDIX
- Flow Control for Full Duplex operation and back pressure for Half Duplex Operation;
- Support Energy-Efficient Ethernet (EEE) function (IEEE802.3az);
- Supports a abundant lineup of L2 features, including 802.1Q tag VLAN, Port Mirroring, STP/RSTP/MSTP, Link Aggregation Control Protocol and 802.3x Flow Control function;
- Web, CLI (Console Port, Telnet, SSH), SNMP and RMON bring abundant management policies;

Specifications

Model	NSW5110-24GT4GP-IN
Software Specification	

Ethernet	<p>Support frame format: Ethernet II, Support Gigabit SFP,</p> <p>Support flow control, Support line order (MDIX/MDI),</p> <p>Support link aggregation,</p> <p>Support Jumbo Frame Size 9K,</p> <p>Support port rate adjustment,</p> <p>Auto, 10M full/half duplex, 100M full/half duplex, 1000M full/half duplex</p>
IEEE802.1d STP	Support IEEE802.1d STP
IEEE802.1w RSTP	Support IEEE802.1w RSTP
MSTP	<p>Support standard 802.1s MSTP,</p> <p>Support 64 MSTP instances</p>
STP Optional Features	<p>Support port fast,</p> <p>Support BPDU filter,</p> <p>Support BPDU guard,</p> <p>Support hello-time,</p> <p>Support max age,</p> <p>Support forward delay,</p> <p>Support max hops,</p> <p>Support TC ignore</p>
MSTP Port Optional Features	<p>Support port fast,</p> <p>Support BPDU filter,</p> <p>Support BPDU guard,</p> <p>Support TC guard,</p> <p>Support TC filter,</p> <p>Support Auto edge,</p> <p>Support TC protection,</p> <p>Support compatibility mode</p>
AP	<p>Support Flow-Balance Methoddst-ip Destination IP address; dst-mac Destination MAC address; src-dst-ip Source and destination IP address; src-dst-mac Source and destination MAC address; src-ip Source IP address; src-mac Source MAC address,</p> <p>Support AP member port that is included in each AP.</p>
Storm Control	<p>Support multicast storm control, Support control granularity (percentage and kbps are values for 64-byte datagram) 64 kbps, Support broadcast storm control,</p> <p>Support unicast storm control</p>

Mirroring	<p>Support Many-to-one mirror,</p> <p>Support Stream-based mirroring,</p> <p>Support number of mirror groups 4</p>
VLAN	<p>Support whether to allow VLAN 1 to be deleted on the trunk port,</p> <p>Support port based VLAN,</p> <p>Support GVRP,</p> <p>Support the number of VLAN that can support be created 4094,</p> <p>support Mac-VLAN,</p> <p>Support Subnet-VLAN,</p> <p>Support Protocol VLAN,</p> <p>Support VLAN maps</p>
MAC Address	<p>Support gentries MAC address numbers 8K,</p> <p>Support static MAC address numbers 1024,</p> <p>Support filtering MAC address numbers 1024,</p> <p>Support check and delete address table,</p> <p>Support filtering address</p> <p>,</p> <p>Support static address and dynamic learning address</p>
LLDP	Support LLDP
ONVIF	<p>Support ONVIF detect,</p> <p>Support ONVIF server</p>
IGMP Snooping	<p>Support IGMP snooping groups,</p> <p>Support IGMP V1, V2 snooping,</p> <p>Support source IP check,</p> <p>Support multicast policy and filtering,</p> <p>Support IGMP fast Leave</p>
Port Limit	<p>Support egress speed limit granularity,</p> <p>Support Ingress speed limit,</p> <p>Support egress speed limit</p>
ARP	<p>Support Anti-ARP gateway spoofing,</p> <p>Support filtering IP port,</p> <p>Support free ARP protection,</p> <p>Support source MAC check, Support ARP Detection,</p> <p>Support IP and Mac static binding,</p> <p>Support ARP trust port</p>

Network Tool	Support Ping, Support traceroute
ACE Capacities	Support the input direction is associated with the physical port
ACL	Support IP standard ACL, Support IP extended ACL, Support professional ACL, Support Mac extended ACL, Support global ACL, Support Time-range ACL
QoS	Support QoS hardware queues, Support determine the exit queue according to 802.1p, DSCP, port, Support Stream-based 802.1p Re-marking, Support Stream-based queue maps, Support SP, Support WRR, Support RR, Support WFQ
Port Security	Support Mac filtering time, Support White-list data, Support clear Mac address table, Support Mac address binding, Support max Mac numbers settings, Support blacklist data, Support violation mode
Port Isolation	Support
LOOPBACK	Support
DAI	Support software DAI entries
SNMP	Supporting version (SNMPV1, V2c, V3)
Web Management	Support HTTP access
RMON	Support RMON (1, 2, 3, 9)
System Upgrade	Support system upgrade or page upgrade via TFTP
Save Configuration	Support save configuration
Configuration Management	Support Import, export, backup configuration, restore factory configuration
Syslog/Debug	Support Syslog/Debug

Security Function	Support
Basic Characteristics	Support login authentication (password, none)
Password Security	Support static password encryption transmission, storage, Support strong password and password minimum length check
Radius	Support radius, Support specify multiple groups of servers IP
Tacacs+	Support specify multiple groups of servers IP , Support Tacacs+
SSH	Support SSHv2.0
Anti-dos Attack	Support Interrupting land attack packets and illegal TCP packets
Dot1x	Support 802.1X, Support port base, Support Mac base, Support MAB, Support multiple account switching
Defense Gateway ARP Spoofing	Support defense gateway ARP spoofing
IP Source Guard	Support IP source guard
CPP	Support hardware CPP
ARP Check	Support leverage IP+MAC data binding of IP source guard, Support IP + MAC data binding using DHCP snooping, Support leverage 1X IP+MAC data binding, Support trusted ARP
DHCP Relay	Support allow configuration of the number of servers
DHCP Snooping	Support Option82, Support trust port configuration, Support IP, MAC binding table(IP Source Guard), Support bind to logical ports (including physical interfaces), Support software binding database capacity, Support bind to VLAN

DHCP Server	Support binding table configuration, Support address pool configuration
Telnet	Support Telnet, Support maximum number of connections
TFTP	Support TFTP client
FTP	Support FTP server, Support FTP client
ERPS	Support delete ERPS loop, Support ERPS loop configuration, Support ERPS time configuration
Static And Dynamic LACP Link Aggregation	Support LACP configuration, Support Load-Balance Method; dst-ip Destination IP address; dst-mac Destination MAC address; src-dst-ip Source and destination IP address; src-dst-mac Source and destination MAC address; src-ip Source IP address; src-mac Source MAC address, Support link aggregation groups, Support max link aggregation numbers of each link aggregation group, Support link aggregation port configuration

Hardware Specification

Ports Type	24×1000Mbps ports (RJ45)+2×1000Mbps Fiber(SFP) ports+2G Combo ports
Standards	IEEE802.3, IEEE802.3u, IEEE802.3z, IEEE802.3ab, IEEE802.3x
Switching capacity	56 Gbps
Forwarding performance	41.66Mpps
Packet Buffer	4 M bit
MAC	8K
Dimensions (W×D×H)	440 × 208 × 44 mm
Weight	<3.6 kg
Power supply	AC: 100-240 V, 50/60 Hz
Storage Temperature	-40 °C to 70 °C
Operating temperature	0 °C to 40 °C (32 °F to 104 °F)

Operating humidity	10%~90% (non-condensing)
Storage humidity	5%~90% (non-condensing)
Indicator	POWER Steady on: AC input is normal, POWER Off: No AC input, LINK/ACT Steady on: Linked, LINK/AC Green light: connected to 1000 Mbps devices, LINK/ACT Flashing: Transmitting data
Mean Time Between Failure (MTBF)	>50000 hours

Ordering Info

Product Model	Description
NSW5110-24GT4GP-IN	Ethernet Switch

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China (Zhejiang) Pilot Free Trade Zone, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.