

5MP HD IR VF Dome Network Camera

IPC3635SR4-ADZK-H



Features

- High quality image with 5 MP, 1/2.7" CMOS sensor
- 5 MP (2880 × 1620)@25/20 fps; 4 MP (2560 × 1440)@25/20 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
- Oltra 265, H.265, H.264, MJPEG
- 120 dB true WDR technology enables clear image in strong light scene
- Supports 9:16 corridor mode
- Smart IR, up to 40 m (131.2 ft.) IR distance
- MicroSD, up to 256 GB
- IP67 protection
- Supports PoE power supply
- 3-axis

Specifications

Model	IPC3635SR4-ADZK-H
BOM	
ВОМ	0235U69L

DATASHEET

Dimensions

UNV



Accessories

TR-JB03-H-IN Junction Box for Metal Turret Camera(Support wiring from behind)



TR-A01-IN NPT 3/4'' Waterproof Cable Gland



TR-JB07/WM03-F-IN Wall Mounting Assembling Bracket with Back Hole for 3 Inch Hemisphere TR-WM03-B-IN Wall Mounting Assembling Bracket for 3 Inch Hemisphere



TR-UP06-IN Universal Pole Mounting Bracket





TR-UC08-C Bullet&Dome Corner Mounting Bracket



UNV

DATASHEET

TR-SE24-IN

Dome Pendent Mounting Pole 200mm



TR-SE24-A-IN

Dome Pendent Mounting Pole 500mm Do

TR-CM24-IN

Dome Pendent Mounting Bracket(Indoor)



Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

 ${\it Email: overseas business} @uniview.com; global support @uniview.com \\$

http://www.uniview.com

©2024-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.