

## 5MP ColourHunter Fixed Bullet Analog Camera UAC-B115-AF28(40)-W



## Overview

UAC-B115-AF28(40)-W is a 5MP ColourHunter fixed bullet analog camera with a high-performance 1/2.7-inch CMOS sensor. It supports TVI/AHD/CVI/CVBS, which effectively enhances product adaptability and diversity of networking solutions. With SYV-75-3 or other coaxial cable types, the camera can achieve low-cost, long-distance, and anti-interference mega-pixel HD video transmission without time delay. The camera also supports audio input and synchronous transmission of audio and video.

## Features

- 5MP high quality image
- TVI/AHD/CVI/CVBS
- Supports white light illumination, 24/7 color images
- Supports 180° horizontal flip, 180° vertical flip
- OSD configuration menu, easy to operate
- IP67 waterproof and dustproof design, high reliability
- OSD configuration menu in 11 languages
- Built-in microphone for high quality audio transmission via coaxial cables


## Specifications

| Model             | UAC-B115-AF28-W                               | UAC-B115-AF40-W |
|-------------------|-----------------------------------------------|-----------------|
| Camera            |                                               |                 |
| Max Resolution    | 5 MP                                          |                 |
| Sensor Size       | 1/2.7" CMOS                                   |                 |
| Min. Illumination | 0.01 lux (F1.6, AGC ON)0 lux (white light on) |                 |
| Lens              |                                               |                 |

|                         |                                                                                                                                                                                                                                  |        |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| Focus                   | 2.8 mm                                                                                                                                                                                                                           | 4.0 mm |
| Lens Mount              | M12                                                                                                                                                                                                                              |        |
| Angle of View (H)       | 110.0°                                                                                                                                                                                                                           | 90.0°  |
| Angle of View (V)       | 57.0°                                                                                                                                                                                                                            | 48.0°  |
| Angle of View (D)       | 130.0°                                                                                                                                                                                                                           | 109.1° |
| Illuminator             |                                                                                                                                                                                                                                  |        |
| Illuminator Number      | One white-light illuminator                                                                                                                                                                                                      |        |
| Illumination Distance   | 20m                                                                                                                                                                                                                              |        |
| Lifetime                | ≥ 60000 hours                                                                                                                                                                                                                    |        |
| Video                   |                                                                                                                                                                                                                                  |        |
| Resolution              | 5MP@25fps: 2880(H)×1620(V); 5MP@20fps: 2592(H)×1944(V); 5MP@12.5fps: 2592(H)×1944(V)4MP: 2560(H)×1440(V)1080P: 1920(H)×1080(V)                                                                                                   |        |
| Frame Rate              | TVI: 5MP@20fps (default), 5MP@12.5fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fpsAHD: 5MP@20fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fpsCVI: 5MP@25fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fpsCVBS: PAL, NTSC |        |
| Shutter Time            | PAL: 1/25s-1/50000s, NTSC: 1/30s-1/50000s                                                                                                                                                                                        |        |
| Image                   |                                                                                                                                                                                                                                  |        |
| Exposure Mode           | Four modes: Global (default), BLC, HLC, DWDR                                                                                                                                                                                     |        |
| Day/Night               | 24/7 color images                                                                                                                                                                                                                |        |
| Digital Noise Reduction | 2D                                                                                                                                                                                                                               |        |
| White Balance           | Two modes: Auto (default), Manual                                                                                                                                                                                                |        |
| WDR                     | DWDR                                                                                                                                                                                                                             |        |
| Flip                    | Supports 180°horizontal flip, 180°vertical flip                                                                                                                                                                                  |        |
| Digital Defog           | N/A                                                                                                                                                                                                                              |        |
| Audio                   |                                                                                                                                                                                                                                  |        |
| Built-in Mic            | Support                                                                                                                                                                                                                          |        |
| Camera Audio            | TVI: 5MP@20fps, 5MP@12.5fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fpsCVI: 5MP@25fps, 4MP@25fps, 4MP@30fps                                                                                                                  |        |
| Interface               |                                                                                                                                                                                                                                  |        |
| Power Interface         | 5.5 mm Power Interface                                                                                                                                                                                                           |        |
| Video Output            | BNC, supports TVI/AHD/CVI/CVBS                                                                                                                                                                                                   |        |
| Operating Environment   |                                                                                                                                                                                                                                  |        |
| Temperature             | -30 °C to 60 °C (-22 °F to 140 °F)                                                                                                                                                                                               |        |
| Humidity                | ≤ 95% RH (non-condensing)                                                                                                                                                                                                        |        |
| Surge Protection        | 4kV for power&4kV for video output interfaces                                                                                                                                                                                    |        |
| General                 |                                                                                                                                                                                                                                  |        |
| Power                   | DC 12 V ± 25%                                                                                                                                                                                                                    |        |
| Power Consumption       | MAX 2.3W                                                                                                                                                                                                                         |        |
| Mount                   | Corner Mount&Pole Mount                                                                                                                                                                                                          |        |
| Dimensions              | 142mm*63mm*65mm (L*W*H)                                                                                                                                                                                                          |        |
| Material                | Graphene + Plastic                                                                                                                                                                                                               |        |
| Weight                  | 150g(0.33lb)                                                                                                                                                                                                                     |        |

|                   |                                                                                                                                          |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| OSD Menu Language | 11 Languages: English, German, Spanish (Latin America), French, Italian, Japanese, Korean, Polish, Portuguese (Brazil), Russian, Turkish |
| Certification     |                                                                                                                                          |
| EMC               | CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035), FCC (FCC 47 CFR part15 B)                                                   |
| Safety            | CE-LVD (EN 62368-1)                                                                                                                      |
| Environment       | CE-RoHS (2011/65/EU; (EU) 2015/863); WEEE (2012/19/EU)                                                                                   |
| Protection        | IP67 (IEC 60529)                                                                                                                         |

## Dimensions



## Accessories

### TR-JB05-A-IN

Small Bullet Junction Box(Support wiring from behind,Square)



### TR-UP06-B-IN

Bullet Pole Mounting Bracket



### TR-UP06-C-IN

Pole Mounting Bracket for Bullet Junction Box Only



TR-A01-IN

NPT 3/4" Waterproof Cable Gland



TR-UC08-C

Bullet&Dome Corner Mounting Bracket



PWR-DC1201A-UK

DC12V/1A Wall Plug British Standard  
Power Adapter



PWR-DC1201B-UK

UNV DC12V/1A Wall Plug British Standard  
Power Adapter(Colorful Bag)



PWR-DC1201A-US

DC12V/1A Wall Plug American Standard  
Power Adapter



PWR-DC1201B-US

UNV DC12V/1A Wall Plug American  
Standard Power Adapter(Colorful Bag)



PWR-DC1201A-EU

DC12V/1A Wall Plug European Standard  
Power Adapter



PWR-DC1201B-EU

UNV DC12V/1A Wall Plug European  
Standard Power Adapter(Colorful Bag)



PWR-DC1201A-IND

UNV DC12V/1A Wall Plug Indian  
Standard Power Adapter-Colorful Bag



**Zhejiang Uniview Technologies Co., Ltd.**



<http://www.uniview.com>



[overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China  
(Zhejiang) Pilot Free Trade Zone, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

\*Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.