

General-Purpose CPU Server Datasheet

VS-R5320-B2T@N-IN



Overview

This 2-socket 2U rack server is designed based on 3rd-generation Intel® Xeon® Scalable processors. It uses high-performance Intel® C621 series chipsets to deliver robust performance in a limited space and meanwhile provide scalability and high availability.

Features

- High performance
- 3rd-generation Intel® Xeon® Scalable processors.
- 2 standard Gigabit network interfaces for data transmission, 1 optional dual-Gigabit or dual-10GE network interface module for expansion, capable of load balance, link aggregation and redundancy to effectively reduce network latency; 1 Gigabit remote management network interface.
- DDR4 3200MHz RAM frequency, increasing bandwidth by 45% over the previous generation.
- High reliability
- 12 3.5/2.5-inch HDDs, compatible with NVMe SSD, allowing personalized storage configuration.
- 1+1 power redundancy design supports PMBus, module-loss alarm and more to enhance server operation security.
- Low power consumption
- Supports frequency reduction to reduce system power consumption at low system load.
- Adjusts fan speed according to the temperature of thermally critical components to save energy, reduce noise, and improve reliability of fans.

- In line with green energy-saving business demands, the newly-added energy-efficient intelligent speed regulation design can adjust heat dissipation of the whole system according to ambient temperature and actual load, reducing power consumption without compromising performance.

Specifications

Model	VS-R5320-B2T@N-IN
Hardware Parameters	
CPU	Intel_4310_Xeon*2, support 2* 3rd-generation Intel® Xeon® Scalable processors
RAM	32GB*2, total 16 slots
Standard HDD	4T SATA HDD*1
Front HDD expansion	12*2.5/3.5-inch SAS/SATA/SSD HDDs
Network interface	GE*2, supports PCIe network interface expansion
Management	1*1000Mbps network interface dedicated for IPMI remote management
USB	2*USB 3.0 (rear)
VGA	1* VGA interface (rear)
PCI-E card slots	3*PCI-E 4.0 slots
Built-in RAID controller	1 (sold separately)
Power supply	1+1 redundancy
Dimensions	87.8mm(H)x446mm(W)x794mm(D)
Weight	35KG (fully loaded)
Environment temperature	Operating: 5°C to 40°C Non-operating: -40°C to 60°C
Relative humidity	Operating: 35% to 80% Non-operating: 20% to 93%

Ordering Info

Product Model	Config	Description
VS-R5320-B2T	N-IN	2U Universal Mid-end CPU Server

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China (Zhejiang) Pilot Free Trade Zone, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2024-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.