


Harsh PoE Switch

HS2000-4GT2GP-POE-IN



Features


- Support IEEE 802.3af/at standard
- IP40 protection level, high-strength aluminum shell, DIN35 rail installation
- Industrial grade 4-level design, operating temperature from -30~65°C
- Support redundant power supply connection and anti reverse connection

Specifications

Model	HS2000-4GT2GP-POE-IN
Hardware Specification	
Standards	IEEE802.3, IEEE802.3i, IEEE802.3u, IEEE802.3ab, IEEE802.3z
Ports Type	4*10/1000Mbps RJ45 PoE Ports 2*1000Mbps SFP Slots
Switching capacity	12Gbps
Jumbo Frame	10KBytes
Forwarding performance	8.92Mpps
Max.PoE Power	Max capacity: 65W Max capacity for single port: 30W Mode A 1/2 (-), 3/6 (+)
MAC	2K
Transfer Mode	Store-and-forward
Dimensions (W×D×H)	120*87*34mm
Operating Temperature	-30°C to 65 °C

Operating Humidity	10% ~ 95% non-condensing
Storage Humidity	5% ~ 95% non-condensing
Indicator	PWR (Red) Off: Powered off On: Powered on Ports 1-4 /1-8(Green) Slow Flashing: 10/100/1000Mbps Link normal Off: Link blocked Fast Flashing: Data transmitting Ports G5-G6 /G9-G10(Green) On: 10/100/1000Mbps Link normal Off: Link blocked Flashing: Data transmitting
Electrostatic Standard	Air 8KV, Contact 6KV
Surge Protection	Common mode 4KV, Differential mode 2KV
Power Supply	DC:48-57V, powered by adapter. Max.Power 68W . Adapter: AC100-240V, 50/60Hz
Working Mode	V: VLAN mode, ports 1-4 are isolated from each other, communicating with ports 5-6, E: Extend mode, when the PoE port is in Extend mode, ports 1-4 force 10Mbps to extend the transmission distance to 250meters, G: PoE watchdog on
Button	Dual color LED selection: default green (link data), switch yellow LED(PoE)

Dimensions



Unlimited New View

Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



overseasbusiness@uniview.com; globalsupport@uniview.com



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.