UTP Category 6 Cables

CAB-LC3101B-CCA-IN



Specifications

Model	CAB-LC3101B-CCA-IN
Cable	
Product model	CAB-LC3101B-CCA-IN
Test Standard	Fluke Test 90m （channel）
Product specification	Cat6 4×2×0.56mm
Packing length	305±1 m
Crossing backbone	Yes
Rip-cord	Yes
Ambient temperature	-20℃ to 75℃
Conductor	
Material	CCA (19%~23%)
AWG	23
Nom.O.D.(mm)	0.56±0.01 mm
Insulation	
Material	HDPE
Diameter	0.98±0.05mm
Color	Blue/White- Blue, Green/White-Green,Orange/White-Orange,Brown/White-Brown
Sheath	
Material	PVC
External O.D.	6.0±0.4 mm
Thickness	0.5±0.05 mm
Color	White

Surface Printing	
Color	Black
Letter height	3.0±0.3 mm
Print error / Space	1±0.005 m
Packing	
Packing	Box
Once packing dimension	410mm*220mm*410mm

Unlimited New View

Zhejiang Uniview Technologies Co., Ltd.

http://www.uniview.com

overseasbusiness@uniview.com; globalsupport@uniview.com

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

©2026 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.