

Managed Harsh PoE Switch HS5000-4GT2GP-POE-IN



Features

- Support IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3z /ab, IEEE802.1Q, IEEE802.1p, IEEE802.1d/w
- Support PoE power management and PoE Watchdog based on data flow detection
- Support IEEE802.3af (15.4W) and IEEE802.3at (30W)
- Support SNMP v1/v2/v3 Simple Network Management Protocol
- Support IGMP Snooping, static multicast filtering, and MLD Snooping filtering
- Support 802.1x port authentication and AAA authentication to enhance network security
- Support WEB, Telnet, CLI, SSH management
- IP40 protection level, high-strength shell, DIN35 rail installation
- Industrial grade 4-level design, operating temperature from -30°C to 65 °C


Specifications

Model	HS5000-4GT2GP-POE-IN
Hardware Specification	
Standards	IEEE802.3 (Ethernet) IEEE802.3u (Fast Ethernet) IEEE 802.3ab (Gigabit Ethernet) IEEE 802.3z (Gigabit Ethernet Fiber Standard) IEEE802.3x (Flow Control) IEEE 802.1D Spanning Tree Protocol IEEE 802.1w Rapid Spanning Tree Protocol
Ports Type	4*10/1000Mbps RJ45 PoE Ports 2*1000Mbps SFP Slots 1*Console port
Switching capacity	12Gbps
Forwarding performance	8.92Mpps
Packet Buffer	4 M bit
Max.PoE Power	Max capacity: 65W Max capacity for single port: 30W Mode A 1/2 (-), 3/6 (+)
Max.Power	70W
MAC	8K
Transfer Mode	Store-and-forward
Dimensions (W×D×H)	138*108*44mm
Operating Temperature	-30°C to 65 °C
Operating Humidity	10% ~ 95% non-condensing
Storage Humidity	5% ~ 95% non-condensing
Indicator	PWR (Green) Off: Powered off On: Powered on SYS(Green) Flashing: System startup in progress On: System startup completed Ports 1-4/Ports1-8 (Green) Slow Flashing: 10/100/1000Mbps Link normal Off: Link blocked Fast Flashing: Data transmitting Ports 1-4(Yellow) On: PoE powered on Off: PoE powered off Ports G5-G6 (Green) On: 10/100/1000Mbps Link normal Off: Link blocked

	Flashing: Data transmitting
Electrostatic Standard	Common mode 6KV, Differential mode 2KV (Class B)
Surge Protection	Air 8KV, Contact 6KV (Class B)
Power Supply	DC:48-57V, powered by adapter
Button	Dual color LED selection: default green (link data), switch yellow LED(PoE) Long press for 6 seconds to restore factory settings
Software Specification	
Ethernet	Port Switch configuration Port Description configuration Port Speed configuration Port Duplex configuration Port Flow Control configuration Jumbo Frame EEE Fiber Module(DDM) Port Isolation Port Rate-limit Loopback Detection Port Mirroring Storm Control
VLAN	Access/Trunk/Hybrid VLAN Tunnel (Q-in-Q Tunnel) VLAN range 1-4094, maximum active VLAN is 4K Voice VLAN, MAC VLAN, Surveillance VLAN, Protocol VLAN, GVRP
MAC	Dynamic MAC address Static MAC address Filtering MAC Address
Reliability	STP/RSTP/MSTP, BPDU Filter, BPDU Guard, Edge Port
Multicast	IGMP Snooping IGMP V1/V2/V3 Router Port Static IGMP group address IGMP groups filtering Querier MLD Snooping MVR
POE	PoE Temperature PoE Type/Level/Power/Voltage/Current query PoE Switch Configuration PoE Watchdog Configuration PoE power AF/AT adaptation PoE Schedule PoE Port Timer Reboot

DHCP	DHCP Server, IP Pool, Static Binding, Option 43, DHCP Relay,DHCP Snooping(Global/VLAN, Option 82, Circuit ID)
ACL	MAC ACL, IPv4 ACL, IPv6 ACL
IP Route	IPv4 Static Routes IPv6 Static Routes
Maintenance	Console, HTTP/HTTPS, Telnet, SSH, SNMP Mnager IP(Static Address,DHCP Client,Support IPv4 and IPv6 address,Manager VLAN,DNS) SNMP(V1/V2C/V3,Community,V3 User,Group,Trap Host) Syslog
Security	AAA(RADIUS, TACACS+, 802.1X,Base on port/MAC/local/WEB)
QoS	Traffic classification based, Strict priority and WRR Port Priority 802.1P Priority IP TOS Priority IP DSCP Priority Support up to 8 queues per port Priority Remarking

Dimensions



Unlimited New View

Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



overseasbusiness@uniview.com; globalsupport@uniview.com



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.