


UTP Category 6A Cables

UV-UTP6A-300-BC23AWG-DCA-R-W

Section View



Specifications

Model	UV-UTP6A-300-BC23AWG-DCA-R-W
Cable	
Product model	UV-UTP6A-300-BC23AWG-DCA-R-W
Product specification	Cat6A. U/UTP. 4×2×0.55mm
Test Standard	ISO/IEC11801 ED.2 ANSI/TIA-568-C.2
Packing length	305±1 m
Rip-cord	Yes
Crossing backbone	Yes
Ambient temperature	-20°C～75°C
Conductor	
Material	OFC

AWG	23
Nom.O.D.(mm)	0.55±0.005 mm
DC resistance	≤95Ω/km
Insulation	
Material	HDPE
Thickness	0.21+0.03mm
Diameter	0.98±0.05 mm
Color	Blue/White- Blue,Green/White-Green,Orange/White-Orange,Brown/White-Brown
Pitch	
Offset pitch	≤25mm
Cable pitch	≤120mm
Sheath	
Material	LSZH (EN13501-6 DCA)
Fire Resistance	CPR Dca
External O.D.	6.0±0.3 mm
Thickness	0.55±0.15 mm
Color	White
Tensile strength	>10 Mpa
Surface Printing	
Letter height	3.0±0.3 mm
Print error / Space	1±0.005 m
Color	Black
Packing	
Packing	Reel
Once packing dimension	380mm*200mm*200mm

Ordering Info

Product Model	Description
UV-UTP6A-300-BC23AWG-DCA-R-W	Cat6a(UTP),305m,Overseas

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China (Zhejiang) Pilot Free Trade Zone, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2024-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.