

【Datasheet】UNV LAMP-S16@A10-T30-OS 10° Warm Light Strobe Illuminator 20231228 (Public)

LAMP-S16@A10-T30-OS



Features

- Elegant appearance, integrated structure design, safety and convenient.
- Uses high-power LED warm light chip, warm and soft light source, glare-free, avoiding light pollution.
- Supports synchronous video illumination.
- Uniform illumination delivers clear image, no smearing or overexposure.
- Pulse signal self-test, no need for setup, automatic high-frequency illumination based on the digital pulse signal of the camera unit.
- Wide voltage allows AC 176V to 264V mains power supply.
- All-weather operation, applicable to harsh environments.
- IP67 protection level, waterproof and dustproof.

Specifications

Model	LAMP-S16@A10-T30-OS
White light flash	
Color temperature	3000K
White light flash lifetime	>50000h@25°C
硬件参数	

Strobe luminous flux	1400lm@20% duty cycle
Illumination angle	10°
Trigger level	4V to 6V (active high)
Trigger duty ratio	1% to 40%
Response time	≤370μs
Interface	1 power input, 1 strobe trigger input
LED strobe	
Trigger mode	TTL level/switch
Trigger frequency	40Hz to 200Hz
Power consumption	30W
Be in common use	
Bracket rotation angle	-90° to +90°
Power supply	AC176V to 264V, 50/60Hz
Weight	1.4kg
Dimensions (L×W×H)	182mm x 157mm x 71.4mm (without universal bracket)
Ingress protection	IP65

