

## 5MP LightHunter HD IR Fixed Dome Analog Camera UAC-D125-AF28(40)M



### Overview

UAC-D125-AF28(40)M is a 5MP LightHunter HD IR fixed dome analog camera with a high-performance 1/2.7-inch CMOS sensor. It supports TVI/AHD/CVI/CVBS, which effectively enhances product adaptability and diversity of networking solutions. With SYV-75-3 or other coaxial cable types, the camera can achieve low-cost, long-distance, and anti-interference mega-pixel HD video transmission without time delay. It supports IR-cut filter with auto-switch (ICR) and provides color images at daytime and black/white images at night. The camera also supports audio input and synchronous transmission of audio and video.

### Features

- High quality imaging with 5MP resolution
- TVI/AHD/CVI/CVBS
- Supports IR-cut filter with auto-switch (ICR)
- LightHunter monitoring with high-sensitivity sensor
- Supports 180° horizontal/vertical flip
- OSD configuration menu, easy to operate
- Water and dust resistant (IP67) and vandal-resistant (IK10)
- OSD configuration menu in 11 languages
- Built-in microphone for high quality audio transmission via coaxial cables
- Metal base and metal housing
- 3-Axis


### Specifications

| Model  | UAC-D125-AF28M | UAC-D125-AF40M |
|--------|----------------|----------------|
| Camera |                |                |

|                         |                                                                                                                                                                                                                                  |        |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| Max Resolution          | 5 MP                                                                                                                                                                                                                             |        |
| Sensor Size             | 1/2.7" CMOS                                                                                                                                                                                                                      |        |
| Min. Illumination       | 0.005 lux (F1.6, AGC ON)0 lux (IR on)                                                                                                                                                                                            |        |
| Lens                    |                                                                                                                                                                                                                                  |        |
| Focus                   | 2.8 mm                                                                                                                                                                                                                           | 4.0 mm |
| Lens Mount              | M12                                                                                                                                                                                                                              |        |
| Angle of View (H)       | 109.1°                                                                                                                                                                                                                           | 91.3°  |
| Angle of View (V)       | 60.9°                                                                                                                                                                                                                            | 46.1°  |
| Angle of View (D)       | 126.7°                                                                                                                                                                                                                           | 109.6° |
| Illuminator             |                                                                                                                                                                                                                                  |        |
| Illuminator Number      | One IR illuminator                                                                                                                                                                                                               |        |
| Illumination Distance   | 30m                                                                                                                                                                                                                              |        |
| Lifetime                | ≥ 60000 hours                                                                                                                                                                                                                    |        |
| Video                   |                                                                                                                                                                                                                                  |        |
| Resolution              | 5MP@25fps: 2880(H)×1620(V); 5MP@20fps: 2592(H)×1944(V); 5MP@12.5fps: 2592(H)×1944(V)4MP: 2560(H)×1440(V)1080P: 1920(H)×1080(V)                                                                                                   |        |
| Frame Rate              | TVI: 5MP@20fps (default), 5MP@12.5fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fpsAHD: 5MP@20fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fpsCVI: 5MP@25fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fpsCVBS: PAL, NTSC |        |
| Shutter Time            | PAL: 1/25s-1/50000s, NTSC: 1/30s-1/50000s                                                                                                                                                                                        |        |
| Image                   |                                                                                                                                                                                                                                  |        |
| Exposure Mode           | Four modes: Global (default), BLC, HLC, DWDR                                                                                                                                                                                     |        |
| Day/Night               | Three modes: Auto (default), Day, Night                                                                                                                                                                                          |        |
| Digital Noise Reduction | 2D                                                                                                                                                                                                                               |        |
| White Balance           | Two modes: Auto (default), Manual                                                                                                                                                                                                |        |
| WDR                     | DWDR                                                                                                                                                                                                                             |        |
| Smart IR                | Support                                                                                                                                                                                                                          |        |
| Flip                    | Supports 180°horizontal flip, 180°vertical flip                                                                                                                                                                                  |        |
| Digital Defog           | N/A                                                                                                                                                                                                                              |        |
| Audio                   |                                                                                                                                                                                                                                  |        |
| Built-in Mic            | Support                                                                                                                                                                                                                          |        |
| Camera Audio            | TVI: 5MP@20fps, 5MP@12.5fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fpsCVI: 5MP@25fps, 4MP@25fps, 4MP@30fps                                                                                                                  |        |
| Interface               |                                                                                                                                                                                                                                  |        |
| Power Interface         | 5.5 mm Power Interface                                                                                                                                                                                                           |        |
| Video Output            | BNC, supports TVI/AHD/CVI/CVBS                                                                                                                                                                                                   |        |
| Operating Environment   |                                                                                                                                                                                                                                  |        |
| Temperature             | -30°C to 60°C (-22°F to 140°F)                                                                                                                                                                                                   |        |
| Humidity                | ≤ 95% RH (non-condensing)                                                                                                                                                                                                        |        |
| Surge Protection        | 4 KV for power, 4 KV for video output interfaces                                                                                                                                                                                 |        |
| Ingress Protection      | IP67                                                                                                                                                                                                                             |        |
| IK Rating               | IK10                                                                                                                                                                                                                             |        |
| General                 |                                                                                                                                                                                                                                  |        |

|                   |                                                                   |
|-------------------|-------------------------------------------------------------------|
| Power             | DC 12 V $\pm$ 25%                                                 |
| Power Consumption | MAX 3.3W                                                          |
| Mount             | Wall Mount, Pole Mount, Corner Mount, Tilted Mount, Pendant Mount |
| Dimensions        | $\Phi$ 109mm*83mm (diameter*height)                               |
| Material          | Metal                                                             |
| Weight            | 372g(0.82lb)                                                      |

## Dimensions



## Accessories

### TR-JB03-G-IN

Junction Box for Mini Fix-dome(Support wiring from behind)



### TR-SE24-A-IN

Dome Pendent Mounting Pole 500mm



### TR-SE24-IN

Dome Pendent Mounting Pole 200mm



TR-CM24-IN

Dome Pendant Mounting Bracket(Indoor)



TR-A01-IN

NPT 3/4" Waterproof Cable Gland



TR-UM06-E-IN

Slant Mounting Bracket for Fixed Dome



PWR-DC1201A-US

DC12V/1A Wall Plug American Standard  
Power Adapter

PWR-DC1201B-EU

UNV DC12V/1A Wall Plug European  
Standard Power Adapter(Colorful Bag)

TR-JB07/WM03-G-IN

Wall Mounting Assembling Bracket For 32  
Fix-dome&Mini Fix-dome&Plastic Turret  
Camera

TR-UP06-IN

Universal Pole Mounting Bracket



PWR-DC1201A-UK

DC12V/1A Wall Plug British Standard  
Power Adapter

PWR-DC1201B-US

UNV DC12V/1A Wall Plug American  
Standard Power Adapter(Colorful Bag)

PWR-DC1201A-IND

UNV DC12V/1A Wall Plug Indian  
Standard Power Adapter-Colorful Bag

TR-WM03-D-IN

Wall Mounting Bracket for 32  
Fix-dome&Mini Fix-dome&Plastic Turret  
Camera

TR-UC08-C

Bullet&amp;Dome Corner Mounting Bracket



PWR-DC1201B-UK

UNV DC12V/1A Wall Plug British Standard  
Power Adapter(Colorful Bag)

PWR-DC1201A-EU

DC12V/1A Wall Plug European Standard  
Power Adapter

# Unlimited New View

**Zhejiang Uniview Technologies Co., Ltd.**

-  <http://www.uniview.com>
-  [overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)
-  No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China  
(Zhejiang) Pilot Free Trade Zone, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.  
\*Product specifications and availability are subject to change without notice.  
\*Despite our best efforts, technical or typographical errors may exist in this document.  
Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.