

## UTP Category 6 Cables

# CAB-LC3101B-E4-IN



## Specifications

<b>Model</b>	CAB-LC3101B-E4-IN
<b>Cable</b>	
Product model	CAB-LC3101B-E4-IN
Test Standard	ISO/IEC11801, TIA-568-C.2, Fluke Test 100m (channel)
Product specification	CAT6 4×2×0.53mm
Packing length	305±1 m
Crossing backbone	Yes
Rip-cord	Yes
Ambient temperature	-20°C to 60°C
<b>Conductor</b>	
Material	Solid-Bare Copper
AWG	24
Nom.O.D.(mm)	0.53±0.01 mm
DC resistance	≤95 Ω/km
<b>Insulation</b>	
Material	HDPE
Diameter	0.95±0.05 mm
Color	Blue/White- Blue, Green/White-Green,Orange/White-Orange,Brown/White-Brown
<b>Sheath</b>	
Material	PVC
External O.D.	6.0±0.3 mm

Tensile strength	>13.5 Mpa
Thickness	0.6 ±0.05 mm
Color	Orange (RAL2008)
<b>Surface Printing</b>	
Color	Black
Letter height	3.0±0.3 mm
Print error / Space	1±0.005 m
<b>Packing</b>	
Packing	Carton
Once packing dimension	410mm*210mm*410mm
Twice packing dimension	430mm*465mm*430mm
Twice packing quantity	2

**Zhejiang Uniview Technologies Co., Ltd.**

-  <http://www.uniview.com>
-  [overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)
-  No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China  
(Zhejiang) Pilot Free Trade Zone, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

\*Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.