4MP ANPR LightHunter Wise-ISP Network Bullet Camera

IPS-HC264





Features

- High quality image with 4 MP, 1/1.8" CMOS sensor
- 2688 × 1520@60 fps in the main stream, which can offering more details of fast moving objects
- Ultra 265, H.265, H.264, MJPEG
- ANPR supports capturing and recognizing car license plate according to the set country or area
- Adjustable far and near lights, suitable for different capture situation
- 8 to 32 mm focal lens, suitable for road scenarios
- Wise-ISP technology, comprehensive improvement in image quality
- Audio 2 in and 1 out, Alarm 3 in and 2 out
- Built in heater, support normal start up at low temperature
- Micro SD, up to 512 GB
- DC 12V or PoE (IEEE 802.3at) power supply
- IP67, IK10
- In according to get the best intelligent performance, please refer to engineering survey guide.

Specifications

Model	IPS-HC264@HDX4-IR-I1	IPS-HC264@HDX4-WH-I1
Camera		

DATASHEET

Max Resolution	4 MP		
Sensor	1/1.8" CMOS		
Min. Illiansin eti en	Colour:0.0005 lux (F1.6, AGC ON)	Colour:0.0005 lux (F1.6, AGC ON)	
Min. Illumination	B/W:0.0003 lux (F1.6, AGC ON)	0 lux with Light	
Day /NE-ht	0 lux with IR		
Day/Night	IR-cut filter with auto switch (ICR)		
Shutter	Auto/Manual, 1 to 1/100000 s		
WDR	140 dB		
	Pan: 0° to 360°		
Adjustment Angle	Tilt: 0° to 90°		
	Rotate: 0° to 360°		
S/N	>56 dB		
Case Type	Bullet		
Lens	1		
Focal Length	8 to 32 mm		
Digital Zoom	16X		
Optical Zoom	4X		
Iris	F1.6		
Field of View (H)	42.6°~15.2°		
Field of View (V)	23.5°~8.9°		
Field of View (D)	52.4°°~17.9°		
Iris Type	P-iris		
DORI			
DORI Distance	124 1m(407.2ft) 400 cm(1020.1ft)		
(Detect)	124.1m(407.3ft)~496.6m(1629.1ft)		
DORI Distance			
(Observe)	49.7m(162.9ft)~198.6m(651.6ft)		
DORI Distance			
(Recognize)	24.8m(81.5ft)~99.3m(325.8ft)		
DORI Distance			
(Identify)	12.4m(40.7ft)~49.7m(162.9ft)		
Illuminator			
Illumination			
Distance (Warm		40 m (131.2 ft)	
Light)			
Illumination			
Distance (IR)	40 m (131.2 ft)		
Wavelength	850 nm		
Video	I		
Frame Rate-Main			
Stream	4MP(2688*1520), Max 60fps		
Video			
Compression	Ultra 265, H.265, H.264, MJPEG		

DATASHEET

Frame Rate-Sub	Stream 2MP(1920*1080), Max 60fps;		
Frame Rate-Third Stream	D1 (720*576), Max 60fps		
Frame Rate Recommendation	2688*1520@60fps+1080P@60fps+D1@60fps		
Video Bit Rate	128 Kbps to 16 Mbps		
U-code	Support		
ROI	Up to 8 areas		
Privacy Mask	Up to 8 areas (8 blacks / 8 mosaics)		
Video Stream	Triple streams		
OSD	Up to 10 OSDs		
Image			
White Balance	Auto,Outdoor,Fine Tune,Sodium Lamp,Locked,Auto2		
Digital Noise Reduction	se 2D/3D DNR		
Smart IR	Support N/A		
Flip	Normal,Flip Vertical,Flip Horizontal,180°,90°Clockwise,90°Anti-clockwise		
HLC	Support		
BLC	Support		
Defog	Digital defog		
Intelligent			
ANPR	Up to 4 car lanes can be set: Support pedestrian, motor vehicle and non motor vehicle image capturing; Support recognizing car license plate more accurately by choosing different country/ region; Support attribute collection: plate number, vehicle type, vehicle color, vehicle brand		
Supports MultipleNorth America: United States, Canada;South America: Mexico, Brazil; EU: France, Spain, Portugal, Ireland, Bulgaria, Latvia, Romania, Slovenia, Poland, Hungary, Serbia, Czech Republic, Slovakia, B Herzegovina, Greece, Croatia, Ukraine; Asia Pacific: South Korea, Indonesia, Malaysia, Singapore, V Bangladesh;Middle East: Iraq, Saudi Arabia, United Arab Emirates, Egypt;			
Capture Speed Range	≤ 120 km/h		
Events			
Basic Detection	Motion detection,Audio detection,Tampering alarm		
General Function	Watermark, IP Address Filtering, Access Policy, ARP Protection, RTSP Authentication, User Authentication, HTTP authentication, Alarm input, Alarm output		
Audio			
Audio Compression	G.711U,G.711A		
Audio Bitrate	120 Kbpc		
	128 Kbps		
Two-way Audio	Support		
Suppression	Support		
Sampling Rate	16KHZ		
Storage			

DATASHEET

Edge Storage	Micro SD, up to 512 GB		
Network Storage ANR,NAS(NFS)			
Network			
Protocols IGMP, RTP, SMTP, IPv4, IPv6, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTSP, RTCP, RTMP, DNS, DDNS, UPnP, HTTP, HTTPS, 802.1x, SNMP, QoS, SSL/TLS, SSH			
Compatible Integration			
User/Host	Up to 32 users. 3 user levels: administrator, common user and operator		
Security	Password Protection, Strong Password, HTTPS Encryption, Export Operation Logs, Basic and Digest Authentication for RTSP, Digest Authentication for HTTP, TLS 1.2, WSSE and Digest Authentication for ONVIF, TLS 1.3		
Client	EZStation, UNV-Link, UNV-Link Pro		
Web Browser			
PTZ			
Home Position Support			
Number of Presets 1024			
Interface			
Audio I/O	2 Input: impedance 1 kΩ, amplitude 2.5 V [p-p], 1 Outpu	t: impedance 600 Ω, amplitude 2.5 V [p-p]	
Alarm I/O	3/2		
Serial Port	1 channel RS485 interface		
Built-in Mic	Support, built-in mic*2		
Built-in Speaker	Support		
Network	1 × RJ45 10 M/100 M/1000 M Base-TX Ethernet		
Certification	1		
EMC CE-EMC (EN 55032:2015+A11:2020+A1:2020,EN 61000-3-3: 2021, EN 50130-4:2011+A1:2014) FCC (FCC CFR 47 part15 B, ANSI C63.4 2014)		3:2013+A1:2019+A2:2021,EN IEC 61000-3-2: 2019+A1:	
Safety	EN IEC 62368-1:2020+A11:2020		
	UL (UL 62368-1, 2nd Ed., Issue Date: 2014-12-01)		
Environment	CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU	J); Reach (Regulation (EC) No 1907/2006)	
Protection	IP67 (IEC 60529:1989+AMD1:1999+AMD2:2013) IK10 (IEC 62262:2002)		
General			
Power	DC12V(±25%) , PoE+ (IEEE 802.3at)		
Power			
Consumption	Max 19W	Max 21W	
Power Interface	Ø5.5 mm coaxial power plug		
Dimensions	406 x 125 x 130mm(16.0" x 4.9" x 5.1")		
Weight 1.86Kg(4.10lb)			
Working Environment	ng -40°C ~ 70°C (-40°F ~ 158°F). Humidit∨: ≤95% RH (non-condensing)		
Storage Environment	-40°C ~ 70°C (-40°F ~ 158°F). Humidity: ≤95% RH (non-condensing)		

unv

DATASHEET

Surge Protection	6 KV
Reset Button	Support
Heater	Support
RTC	Support
Material	Sun shield: Plastic
	Front cover: Metal
	Body: Metal
Live View	
Maximum	35
Bitstream	35
Maximum	50 Mbps
Bandwidth	So works
OSD Font	Vector
OSD Color	Support
OSD Character	40
Number	40
Other	
Corridor Mode	Support

Dimensions





Accessories

TR-UP06-C-IN

Pole Mounting Bracket for Bullet Junction

Box Only



Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China (Zhejiang) Pilot Free Trade Zone, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

http://www.uniview.com

©2024-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.