


# Single Door Recognition Access Control Controller

## OER-SR12



## Overview

OER-SR12 are high-performance and highly reliable access controllers. The products provide TCP/IP wired network communication interfaces and specialized access control and management functions to fit various complex access control scenarios.

## Features

- TCP/IP communication with secure reliability.
- Large capacity: Supports up to 42,000 cards and 200,000 events.
- Different mounting holes for easy installation.
- Supports remote upgrade.
- Supports real-time monitoring configuration.
- Supports issuing cards using card readers.

## Specifications

Model	OER-SR12
Hardware Specification	
Dimensions (L x W x H)	235mm x 305mm x 76mm
Weight	2.2KG
Door Control	1 door
Card Reader	2
Wiegand Input Interface (Max DC14V Withstand Voltage)	2
Wiegand Format	WG18/26/34/66
Relay Output	1 set (7A)

Door Magnetic Port	1
Fire Module Expansion Port	1
Operating Environment	Indoor (-10°C to +65°C)
Power Supply	AC 100V to 240V(50Hz or 60Hz)
Mount	Wall mount
Basic Business	
Communication Mode	TCP/IP
Specification Index	
Card Capacity	42000
Event Capacity	200000

## Ordering Info

Product Model	Description
OER-SR12	Single Door Recognition Access Control Controller

## Accessories

### OEC-R3H-M

Wall Mounted Mifare Card Reader



### OEC-R3H-MK

Wall Mounted Mifare Keyboard Card Reader



### OEA-ML12-280

Single Door Electromagnetic Lock 280KG



### OEA-ML22-280

Double Door Electromagnetic Lock 280KG



### OEP-GP2

Open Door Button



### OEP-GM5

Open Door Button



### OEP-GM6-R

Infrared Induction Switch Button



### OEP-GP6

Emergency Exit Button



### OEK-M11

Mifare 卡



## Dimensions



- 3