

UTP Category 5E Cables

CAB-LC2100A-ECA-IN



Specifications

Model	CAB-LC2100A-ECA-IN
Cable	
Product model	CAB-LC2100A-ECA-IN
Test Standard	ISO/IEC11801, TIA-568-C.2, Fluke Test 100m (channel)
Product specification	Cat5e 4×2×0.5mm, CPR ECA
Packing length	305±1 m
Rip-cord	Yes
Ambient temperature	-20°C to 60°C
Conductor	
Material	Solid-Bare Copper
AWG	24
Nom.O.D.(mm)	0.5±0.01 mm
DC resistance	≤95 Ω/km
Insulation	
Material	HDPE
Diameter	0.9±0.05 mm
Color	Blue/White- Blue, Green/White-Green,Orange/White-Orange,Brown/White-Brown
Sheath	
Material	LSZH(CPR Eca)
External O.D.	5.1±0.3 mm
Tensile strength	>10 Mpa


Thickness	0.55±0.05 mm
Color	Gray(RAL7046)
Surface Printing	
Color	Black
Letter height	3.0±0.3 mm
Print error / Space	1±0.005 m
Packing	
Packing	Carton
Once packing dimension	350mm*216mm*350mm
Twice packing dimension	370mm*460mm*370mm
Twice packing quantity	2

Unlimited New View

Zhejiang Uniview Technologies Co., Ltd.

 <http://www.uniview.com>

 overseasbusiness@uniview.com; globalsupport@uniview.com

 No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.