

Unmanaged Ethernet Switch

NSW1010-5T-IN

Overview

The NSW1010 series unmanaged Ethernet switch is a plug-and-play device with no configuration required. The fanless silent design completely eliminates the loud noise caused by other small switches used in the office. The small size and exquisite appearance save the space effectively. It can be widely used in industries such as network video management, hotels, campuses, small and medium-sized enterprises network, etc.



Features

- Supports IEEE802.3 and IEEE802.3u standards.
- Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port.
- Supports auto MDI/MDIX.
- Supports IEEE802.3 flow control for full-duplex mode and backpressure for half-duplex mode.

Specifications

| Model | NSW1010-5T-IN | |
|------------------------|----------------------------|--|
| Hardware Specification | | |
| Ports Type | 5 x 10/100Mbps port (RJ45) | |

1



| Network Media | 10Base-T: Cat3, 4, 5 or higher UTP/STP (≤100m) 100Base-TX: Cat5 or higher UTP/STP (≤100m) |
|------------------------|--|
| Switching capacity | 1Gbps |
| Forwarding performance | 0.744Mpps |
| MAC | 2K |
| Jumbo Frame | 15K |
| Transfer Mode | Store-and-forward |
| Dimensions (W×D×H) | Product: 92*51*21.5mm Packaging: 93*82*51mm |
| Carton Information | Carton dimensions: 435*280*395mm Carton quantity: 100PCS Carton weight: 14.2kg |
| Weight | Product: 0.062kg Packaging: 0.132kg |
| Power Supply | Adapter input voltage: AC 100V to 240V Switch input voltage: 5V, 1A |
| Mount Method | Desktop mount, wall mount |
| Cooling Fans | 0 |
| Operating temperature | 0 °C to 40 °C (32 °F to 104 °F) |
| Operating humidity | 10%~90% (non-condensing) |
| Storage Temperature | -20°C to 70°C |
| Storage Humidity | 5% to 90% RH, noncondensing |
| Indicator | POWER Steady on: AC input is normal, POWER Off: No AC input, LINK/ACT Off: No link, LINK/ACT Flashing: Transmitting data, LINK/ACT Steady on: Linked |

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: overseas business@uniview.com; global support@uniview.com

http://www.uniview.com

©2024 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

 ${}^{*}\operatorname{Product}$ specifications and availability are subject to change without notice.





*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.