

# 4MP WDR LightHunter IR Network Dome Camera IPC3234SA-AHDZK-PI-I1



## Features

- High quality image with 4 MP, 1/2.8" CMOS sensor
- 2688 × 1520@60 fps in the main stream, delivers detailed live while 60 fps keeping it smooth and closer to the real image
- Motorized lens with P-iris, supports accurate control of exposure
- Ultra 265, H.265, H.264, MJPEG
- Smart intrusion prevention, supports false alarm filtering, including cross line, intrusion, enter area, leave area detection
- People counting, supports people flow counting and crowd density monitoring, suitable for different statistical scenarios
- LightHunter technology ensures ultra-high image quality in low-light environment
- Up to 130 dB optical WDR (wide dynamic range)
- DC 12 V, PoE (IEEE 802.3af) power supply
- Alarm I/O: 1/1, audio I/O: 1/1
- IP67, IK10
- \*Intelligent function supported when frame rate is below 30 fps

## Specifications


| Model             | IPC3234SA-AHDZK-PI-I1                          |
|-------------------|------------------------------------------------|
| Camera            |                                                |
| Max Resolution    | 4 MP                                           |
| Sensor            | 1/2.8" CMOS                                    |
| Min. Illumination | Color: 0.003 Lux (F1.6, AGC ON), 0 Lux with IR |

|                            |                                                                                                                                                                                      |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Day/Night                  | IR-cut filter with auto switch (ICR)                                                                                                                                                 |
| Shutter                    | Auto/Manual, 1 to 1/100000 s                                                                                                                                                         |
| WDR                        | 130 dB                                                                                                                                                                               |
| Adjustment Angle           | Pan: 0° to 355°, Tilt: 0° to 70°, Rotate: 0° to 355°                                                                                                                                 |
| S/N                        | >56 dB                                                                                                                                                                               |
| Lens                       |                                                                                                                                                                                      |
| Focal Length               | 2.7 to 13.5 mm                                                                                                                                                                       |
| Optical Zoom               | 5X                                                                                                                                                                                   |
| Iris                       | F1.6                                                                                                                                                                                 |
| Field of View (H)          | 98.7° to 31°                                                                                                                                                                         |
| Field of View (V)          | 52.6° to 18°                                                                                                                                                                         |
| Field of View (D)          | 116.5° to 35.8°                                                                                                                                                                      |
| Iris Type                  | P-iris                                                                                                                                                                               |
| DORI                       |                                                                                                                                                                                      |
| DORI Distance (Lens)       | 2.7 to 13.5 mm                                                                                                                                                                       |
| DORI Distance (Detect)     | 74.3 m to 229.5 m (243.6 ft. to 753.0 ft.)                                                                                                                                           |
| DORI Distance (Observe)    | 29.7 m to 91.8 m (97.4 ft. to 301.2 ft.)                                                                                                                                             |
| DORI Distance (Recognize)  | 14.9 m to 45.9 m (48.7 ft. to 150.6 ft.)                                                                                                                                             |
| DORI Distance (Identify)   | 7.4 m to 23.0 m (24.3 ft. to 75.5 ft.)                                                                                                                                               |
| Video                      |                                                                                                                                                                                      |
| Video Compression          | Ultra 265, H.265, H.264, MJPEG                                                                                                                                                       |
| Video Bit Rate             | 128 Kbps to 16 Mbps                                                                                                                                                                  |
| U-code                     | Support                                                                                                                                                                              |
| ROI                        | Up to 8 areas                                                                                                                                                                        |
| Video Stream               | Triple streams                                                                                                                                                                       |
| Privacy Mask               | Up to 8 areas (8 blacks / 8 mosaics)                                                                                                                                                 |
| OSD                        | Up to 10 OSDs                                                                                                                                                                        |
| Frame Rate-Main Stream     | 4 MP (2688 × 1520), max. 60 fps                                                                                                                                                      |
| Frame Rate-Sub Stream      | 1080P (1920 × 1080), max. 60 fps                                                                                                                                                     |
| Frame Rate-Third Stream    | D1 (720 × 576), max. 60 fps                                                                                                                                                          |
| Intelligent                |                                                                                                                                                                                      |
| Smart Intrusion Prevention | Cross line detection, intrusion detection, enter area detection, leave area detection (support false alarm filtering and the classification of human, non-motor vehicle and vehicle) |
| People Counting            | Support people flow counting and crowd density monitoring                                                                                                                            |
| Image                      |                                                                                                                                                                                      |
| White Balance              | Auto, Outdoor, Fine tune, Sodium lamp, Locked, Auto2                                                                                                                                 |
| Digital Noise Reduction    | 2D/3D DNR                                                                                                                                                                            |
| Flip                       | Flip vertical, Flip horizontal, Normal, 180°, 90° Clockwise, 90° Anti-clockwise                                                                                                      |
| HLC                        | Support                                                                                                                                                                              |
| BLC                        | Support                                                                                                                                                                              |
| Defog                      | Digital defog                                                                                                                                                                        |
| Events                     |                                                                                                                                                                                      |
| Basic Detection            | Motion detection, Audio detection, Tampering alarm, Ultra motion detection                                                                                                           |

|                            |                                                                                                                                                                                                                     |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General Function           | Watermark, IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication, Alarm input, Alarm output                                                            |
| <b>Audio</b>               |                                                                                                                                                                                                                     |
| Audio Compression          | G.711U, G.711A                                                                                                                                                                                                      |
| Audio Bitrate              | 128 Kbps                                                                                                                                                                                                            |
| Two-way Audio              | Support                                                                                                                                                                                                             |
| Suppression                | Support                                                                                                                                                                                                             |
| Sampling Rate              | 16KHZ                                                                                                                                                                                                               |
| <b>Storage</b>             |                                                                                                                                                                                                                     |
| Edge Storage               | MicroSD, up to 512 GB                                                                                                                                                                                               |
| Network Storage            | ANR, NAS (NFS)                                                                                                                                                                                                      |
| <b>Network</b>             |                                                                                                                                                                                                                     |
| Protocols                  | SSH, IGMP, RTP, RTCP, SMTP, IPv4, IPv6, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTSP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, 802.1x, SNMP, QoS, SSL/TLS                                                            |
| Compatible Integration     | ONVIF (Profile S, Profile G, Profile T, Profile M), API, SDK                                                                                                                                                        |
| User/Host                  | Up to 32 users. 3 user levels: administrator, common user and operator                                                                                                                                              |
| Security                   | TLS 1.3, Password Protection, Strong Password, HTTPS Encryption, Export Operation Logs, Basic and Digest Authentication for RTSP, Digest Authentication for HTTP, TLS 1.2, WSSE and Digest Authentication for ONVIF |
| Client                     | UNV-Link, UNV-Link Pro, EZStation                                                                                                                                                                                   |
| Web Browser                | Plug-in required live view: IE 10+, Chrome 45+, Firefox 52+, Edge 79+                                                                                                                                               |
| <b>Illuminator</b>         |                                                                                                                                                                                                                     |
| Illumination Distance (IR) | 40 m (131.2 ft.)                                                                                                                                                                                                    |
| IR On/Off Control          | Auto/Manual                                                                                                                                                                                                         |
| <b>Interface</b>           |                                                                                                                                                                                                                     |
| Audio I/O                  | 1 Input: impedance 1 k $\Omega$ , amplitude 2.5 V [p-p], 1 Output: impedance 600 $\Omega$ , amplitude 2.5 V [p-p]                                                                                                   |
| Alarm I/O                  | 1/1                                                                                                                                                                                                                 |
| Serial Port                | 1 $\times$ RS485                                                                                                                                                                                                    |
| Built-in Mic               | Built-in dual-mic                                                                                                                                                                                                   |
| Built-in Speaker           | N/A                                                                                                                                                                                                                 |
| Network                    | 1 $\times$ RJ45 10 M/100 M Base-TX Ethernet                                                                                                                                                                         |
| <b>Certification</b>       |                                                                                                                                                                                                                     |
| EMC                        | CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 50130)<br>FCC-SDoC (47 CFR Part15, Subpart B)                                                                                                                  |
| Safety                     | CE LVD (EN IEC 62368-1)<br>UL (UL 62368-1)                                                                                                                                                                          |
| Environment                | CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU)                                                                                                                                                                |
| Protection                 | IP67 (IEC 60529)<br>IK10 (IEC 62262)                                                                                                                                                                                |
| <b>General</b>             |                                                                                                                                                                                                                     |
| Power                      | DC 12 V ( $\pm$ 25%), PoE (IEEE 802.3af)                                                                                                                                                                            |
| Power Consumption          | Max. 8 W                                                                                                                                                                                                            |
| Power Interface            | $\varnothing$ 5.5 mm coaxial power plug                                                                                                                                                                             |

|                     |                                                                         |
|---------------------|-------------------------------------------------------------------------|
| Dimensions          | Ø148 mm × 111.4 mm (Ø5.8" × 4.4") (Ø × H)                               |
| Weight              | 0.95 kg (2.09 lb.)                                                      |
| Working Environment | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing) |
| Storage Environment | -40 °C to 70 °C (-40 °F to 158 °F), Humidity: ≤ 95% RH (non-condensing) |
| Surge Protection    | 6 KV                                                                    |
| Reset Button        | Support                                                                 |

## Dimensions



## Accessories

### TR-JB04-C-IN

Junction Box for 323 Series  
Fix-dome(Support wiring from behind)



### TR-JB07/WM04-B-IN

4 Inch Back Hole Hemisphere Wall  
Mounting Assembling Bracket



### TR-WM04-IN

4 Inch Hemisphere Wall Mounting Bracket



TR-FM152-A-IN

In-ceiling Bracket for 323 Series  
Fix-dome



TR-SM04-IN

Switch Box Adapter for 323 Series  
Fix-dome



TR-A01-IN

NPT 3/4" Waterproof Cable Gland



TR-UP06-IN

Universal Pole Mounting Bracket



TR-UC08-C-V2

Bullet&Dome Corner Mounting Bracket



#### Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



[overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

\*Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.