Ethernet Low Power PoE Switches

NSW2020-24T1GT1GC-LPOE-IN



Features

- Multiple working modes to address your business needs: Default(Normal mode), VLAN(Secure mode), EXTEND(Surveillance mode)
- Support port traffic control
- Support for secure mode, all downlink ports can communicate only with uplink ports
- Up to 250m transmission distance on surveillance mode
- Support buffer optimization
- All metal housing, safe and reliable

Specifications

Model	NSW2020-24T1GT1GC-LPOE-IN	
Hardware Specification		
Ports Type	24×100Mbps PoE ports (RJ45)+1×1000Mbps Gigaethernet ports +1×1000Mbps Combo ports	
Switching capacity	8.8 Gbps	
Packet Buffer	4 M bit	
МАС	16K	
Forwarding performance	6.55Mpps	
Prior Ports	1 to 8	
Cooling Fans	1	
Dimensions (W×D×H)	440*250*44mm	
Standards	IEEE802.3, IEEE802.3u, IEEE802.3z, IEEE802.3ab, IEEE802.3x, IEEE802.3af, IEEE802.3at,	
	IEEE802.3az	
Max.Power	250W	
Weight	2.15KG	

UNV		DATASHEET
Operating humidity	10% \sim 90% (non-condensing)	
Working Mode	Default (Normal mode) : All ports can communicate with each other, Extend (Surveillance	
	mode): Transmission distance up to 250 meters. Downlink ports can communicate only with	
	uplink ports, VLAN (Secure mode): Downlink ports can communicate only with uplink ports.	
	Enabling PD keepalive function, the switch will restart the IPC via PoE power when the IPC	
	sends no message in a period of time	
Hardware Specification		
PoE Mode	802.3at/af , ModeB :(4/5+, 7/8-)	

Ordering Info

Product Model	Description
NSW2020-24T1GT1GC- LPOE-IN	Unmanaged Ethernet Switch(PoE)

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

http://www.uniview.com

©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.