

# UTP Category 6 Cables (0.57mm) Datasheet

CAB-LC3100B-IN



## Specifications

Model	CAB-LC3100B-IN
Cable	
Product model	CAB-LC3100B-IN
Test Standard	ISO/IEC11801 ED.2 ANSI/TIA-568-C.2
Product specification	Cat6. U/UTP. 4×2×0.57mm
Packing length	305±1m
Ambient temperature	-20°C~60°C
Rip-cord	Yes
Crossing backbone	Yes
Conductor	

AWG	23
Nom.O.D.(mm)	0.57±0.005 mm
DC resistance	≤95 Ω/km
Material	Solid-Bare Copper
<b>Insulation</b>	
Diameter	1.02±0.05 mm
Material	HDPE
Thickness	0.2±0.02 mm
Color	Blue/White- Blue,Green/White-Green,Orange/White-Orange,Brown/White-Brown
<b>Pitch</b>	
Offset pitch	≤20 mm
Cable pitch	≤120 mm
<b>Sheath</b>	
Material	PVC(complies RoHS/REAC)
Thickness	0.6±0.05 mm
External O.D.	6.2±0.3 mm
Tensile strength	>13.5 Mpa
Color	Blue(RAL5015)
<b>Surface Printing</b>	
Color	Black
Letter height	3.0±0.3 mm
Print error / Space	1±0.005 m
Case number	Yes
<b>Packing</b>	
Packing	Carton
Once packing dimension	420mm*205mm*420mm
Twice packing dimension	450mm*440mm*445mm
Twice packing quantity	2 cases

## Ordering Info

Product Model	Description
CAB-LC3100B-IN	Cat6(UTP)-305m-Overseas

**Zhejiang Uniview Technologies Co., Ltd.**

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China (Zhejiang) Pilot Free Trade Zone, China

Email: [overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)

<http://www.uniview.com>

©2024-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

\*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.