


## 4MP WDR Dual-light VF Turret NetWork Camera IPC3634SR-ADZK-DL3



## Features

- High quality image with 4 MP, 1/3.0" CMOS sensor
- 4 MP (2688 × 1520)@25/20 fps; 4 MP (2560 × 1440)@25/20 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
- Ultra 265, H.265, H.264, MJPEG (Sub Stream Only)
- Wise-ISP technology ensures 24-hour full-color images
- Support cross line, intrusion detection (based on human body detection)
- Support ultra motion detection (human/ vehicle detection)
- 120 dB true WDR technology enables clear image in strong light scene
- Built in mic
- Supports 9:16 corridor mode
- Smart IR, up to 50 m (164.0 ft.) IR distance
- Warm light, up to 50 m (164.0 ft.) warm light distance
- IP67 protection
- MicroSD, up to 512 GB


## Specifications

| Model                              | IPC3634SR-ADZK-DL3                                                                                                                                                                                                                                                                                                                                 |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Camera</b>                      |                                                                                                                                                                                                                                                                                                                                                    |
| Max Resolution                     | 4 MP                                                                                                                                                                                                                                                                                                                                               |
| Sensor                             | 1/3.0" CMOS                                                                                                                                                                                                                                                                                                                                        |
| Min. Illumination                  | Color: 0.002 Lux (F1.6, AGC ON), 0 Lux with IR on                                                                                                                                                                                                                                                                                                  |
| Day/Night                          | IR-cut filter with auto switch (ICR)                                                                                                                                                                                                                                                                                                               |
| Shutter                            | Auto/Manual, 1 to 1/100000 s                                                                                                                                                                                                                                                                                                                       |
| Adjustment Angle                   | Pan: 0° to 360°, Tilt: 0° to 75°, Rotate: 0° to 360°                                                                                                                                                                                                                                                                                               |
| S/N                                | > 52 dB                                                                                                                                                                                                                                                                                                                                            |
| WDR                                | 120 dB                                                                                                                                                                                                                                                                                                                                             |
| <b>Lens</b>                        |                                                                                                                                                                                                                                                                                                                                                    |
| Focal Length                       | 2.8 to 12 mm                                                                                                                                                                                                                                                                                                                                       |
| Iris                               | F1.6                                                                                                                                                                                                                                                                                                                                               |
| Field of View (H)                  | 95.6° to 30.9°                                                                                                                                                                                                                                                                                                                                     |
| Field of View (V)                  | 52.0° to 17.6°                                                                                                                                                                                                                                                                                                                                     |
| Field of View (D)                  | 112.2° to 33.7°                                                                                                                                                                                                                                                                                                                                    |
| Lens Type                          | Motorized                                                                                                                                                                                                                                                                                                                                          |
| Iris Type                          | Fixed                                                                                                                                                                                                                                                                                                                                              |
| <b>DORI</b>                        |                                                                                                                                                                                                                                                                                                                                                    |
| DORI Distance (Lens)               | 2.8 to 12 mm                                                                                                                                                                                                                                                                                                                                       |
| DORI Distance (Detect)             | 63 m to 270 m (206.6 ft. to 885.6 ft.)                                                                                                                                                                                                                                                                                                             |
| DORI Distance (Observe)            | 25.2 m to 108.0 m (82.7 ft. to 354.2 ft.)                                                                                                                                                                                                                                                                                                          |
| DORI Distance (Recognize)          | 12.6 m to 43.2 m (41.3 ft. to 141.7 ft.)                                                                                                                                                                                                                                                                                                           |
| DORI Distance (Identify)           | 6.3 m to 27.0 m (20.7 ft. to 88.6 ft.)                                                                                                                                                                                                                                                                                                             |
| <b>Illuminator</b>                 |                                                                                                                                                                                                                                                                                                                                                    |
| Illumination Distance (Warm Light) | 50 m (164.0 ft.)                                                                                                                                                                                                                                                                                                                                   |
| Illumination Distance (IR)         | 50 m (164.0 ft.)                                                                                                                                                                                                                                                                                                                                   |
| Light On/Off Control               | Auto/Manual                                                                                                                                                                                                                                                                                                                                        |
| Wavelength                         | 850 nm                                                                                                                                                                                                                                                                                                                                             |
| Supplemental Light                 | Dual light                                                                                                                                                                                                                                                                                                                                         |
| <b>Video</b>                       |                                                                                                                                                                                                                                                                                                                                                    |
| Video Compression                  | Ultra 265, H.265, H.264, MJPEG (Sub Stream Only)                                                                                                                                                                                                                                                                                                   |
| H.264 Code Profile                 | Baseline profile, Main profile, High profile                                                                                                                                                                                                                                                                                                       |
| Frame Rate                         | Main Stream: 4 MP (2688 × 1520), max. 25 fps; 4 MP (2560 × 1440), max. 25 fps; 3 MP (2304 × 1296), max. 30 fps; 1080P (1920 × 1080), max. 30 fps; 720P (1280 × 720), max. 30 fps;<br>Sub Stream: 720P (1280 × 720), max. 30 fps; D1 (720 × 576), max. 30 fps; 640 × 360, max. 30 fps; 2CIF (704 × 288), max. 30 fps; CIF (352 × 288), max. 30 fps; |
| Video Bit Rate                     | 128 Kbps to 6144 Kbps                                                                                                                                                                                                                                                                                                                              |
| U-code                             | Support                                                                                                                                                                                                                                                                                                                                            |
| OSD                                | Up to 4 OSDs                                                                                                                                                                                                                                                                                                                                       |

|                         |                                                                                                                                                                                                            |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Privacy Mask            | Up to 4 areas                                                                                                                                                                                              |
| ROI                     | Support                                                                                                                                                                                                    |
| Video Stream            | Dual streams                                                                                                                                                                                               |
| Image                   |                                                                                                                                                                                                            |
| White Balance           | Auto, Outdoor, Fine tune, Sodium lamp, Locked, Auto2, Area white balance                                                                                                                                   |
| Digital Noise Reduction | 2D/3D DNR                                                                                                                                                                                                  |
| Smart IR                | Support                                                                                                                                                                                                    |
| Flip                    | Normal, Flip vertical, Flip horizontal, 180°, 90° Clockwise, 90° Anti-clockwise                                                                                                                            |
| HLC                     | Support                                                                                                                                                                                                    |
| Dewarping               | N/A                                                                                                                                                                                                        |
| BLC                     | Support                                                                                                                                                                                                    |
| Defog                   | Digital defog                                                                                                                                                                                              |
| Events                  |                                                                                                                                                                                                            |
| Basic Detection         | Motion detection, Ultra motion detection (human/ vehicle detection) , Tampering alarm, Audio detection, Cross line (based on human body detection), Intrusion (based on human body detection)              |
| General Function        | Watermark, IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication                                                                              |
| Audio                   |                                                                                                                                                                                                            |
| Audio Compression       | G.711U, G.711A, AAC-LC                                                                                                                                                                                     |
| Audio Bitrate           | G.711U/G.711A: 64 kbps, AAC-LC: 128 kbps                                                                                                                                                                   |
| Two-way Audio           | N/A                                                                                                                                                                                                        |
| Suppression             | Support                                                                                                                                                                                                    |
| Sampling Rate           | G.711U/G.711A: 8 kHz, AAC-LC: 8 kHz, 16 kHz, 48 kHz                                                                                                                                                        |
| Storage                 |                                                                                                                                                                                                            |
| Edge Storage            | MicroSD, up to 512 GB                                                                                                                                                                                      |
| Network Storage         | ANR, NAS (NFS)                                                                                                                                                                                             |
| Network                 |                                                                                                                                                                                                            |
| Protocols               | IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, HTTPS, SMTP, SSL/TLS, QoS, SNMP, PPPoE, UPnP, HTTP, 802.1x                                                        |
| Compatible Integration  | ONVIF (Profile S, Profile G, Profile T), API, SDK                                                                                                                                                          |
| Client                  | EZStation, APP                                                                                                                                                                                             |
| Web Browser             | Plug-in required live view: IE 10+, Chrome 45+, Firefox 52+, Edge 79+, Plug-in free live view: Chrome 57+, Firefox 58+, Edge 16+                                                                           |
| Security                | Password protection, Strong Password, HTTPS encryption, Export operation logs, Basic and Digest Authentication for RTSP, Digest Authentication for HTTP, TLS 1.2, WSSE and Digest Authentication for ONVIF |
| User/Host               | Up to 32 users. 3 user levels: administrator, common user and operator                                                                                                                                     |
| Interface               |                                                                                                                                                                                                            |
| Audio I/O               | N/A                                                                                                                                                                                                        |
| Alarm I/O               | N/A                                                                                                                                                                                                        |
| Serial Port             | N/A                                                                                                                                                                                                        |
| Built-in Mic            | Support                                                                                                                                                                                                    |

|                     |                                                                                                                                                           |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Built-in Speaker    | N/A                                                                                                                                                       |
| WIFI                | N/A                                                                                                                                                       |
| Network             | 1 × RJ45 10 M/100 M Base-TX Ethernet                                                                                                                      |
| Video Output        | N/A                                                                                                                                                       |
| Certification       |                                                                                                                                                           |
| EMC                 | CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 50130-4)<br>FCC (FCC 47 CFR part15 B)                                                                |
| Safety              | CE-LVD (EN 62368-1)<br>UL/CUL (UL 62368-1, CAN/CSA C22.2 No. 62368-1)                                                                                     |
| Environment         | CE-RoHS (2011/65/EU ; (EU) 2015/863) ; WEEE (2012/19/EU)                                                                                                  |
| Protection          | IP67 (IEC 60529)                                                                                                                                          |
| General             |                                                                                                                                                           |
| Power               | DC 12 V±25%, PoE (IEEE 802.3af)                                                                                                                           |
| Power Consumption   | Max. 5.8 W                                                                                                                                                |
| Power Interface     | Ø5.5 mm coaxial power plug                                                                                                                                |
| Dimensions          | Ø129.1 mm × 114.9 mm (Ø5.1" × 4.5") (Ø × H)                                                                                                               |
| Weight              | 0.67 kg (1.48 lb)                                                                                                                                         |
| Working Environment | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)                                                                                   |
| Storage Environment | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)                                                                                   |
| Material            | Metal                                                                                                                                                     |
| Surge Protection    | 4 KV                                                                                                                                                      |
| Web Client Language | 14 Languages: English, Simplified Chinese, Polish, German, Russian, French, Korean, Dutch, Czech, Portuguese, Spanish, Spanish (Europe), Italian, Turkish |

## Dimensions



## Accessories

|                                                                                     |                                                                                     |                                                                                                      |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|
| <b>TR-JB03-H-IN-V2</b><br>Turret Junction Box(Support Wiring From Behind)           | <b>TR-JB03-J-IN</b><br>VF Turret Junction Box(Support Wiring From Behind)           | <b>TR-JB07/WM03-F-IN-V2</b><br>Wall Mounting Assembling Bracket with Back Hole for 3 Inch Hemisphere |
|  |  |                 |
| <b>TR-WM03-B-IN-V2</b><br>3 Inches Dome Wall Mounting Assembling Bracket            | <b>TR-A01-IN</b><br>NPT 3/4" Waterproof Cable Gland                                 | <b>TR-UP06-C-IN-V2</b><br>Pole Mounting Bracket for Bullet Junction Box Only                         |
|  |  |                 |

| TR-UC08-C-V2                                                                      | TR-CM24-IN                                                                        | TR-SE24-A-IN                                                                        |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Bullet&Dome Corner Mounting Bracket                                               | Dome Pendent Mounting Bracket(Indoor)                                             | Dome Pendent Mounting Pole 500mm                                                    |
|  |  |  |
| TR-SE24-IN                                                                        |                                                                                   |                                                                                     |
| Dome Pendent Mounting Pole 200mm                                                  |                                                                                   |                                                                                     |
|  |                                                                                   |                                                                                     |

# Unlimited New View

## Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



[overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2026 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.