

NSW2010-18GT2GP-POE- IN Gigabit Ethernet Switches Datasheet



Features

- Support IEEE802.3 at standard, compatible with IEEE802.3 af by electrical equipment (PD)
- Supports PoE Power up to 30W for each PoE port;
- Auto detect power device; will not burned non-standard PoE device or normal PoE switch;
- Supports port power supply prioritization, guarantee the continuous power supply of key nodes;
- Supports IEEE802.3 x full duplex flow control and Backpressure half duplex flow control;
- Line-speed forwarding, intelligent identification
- Supports storage - and- forward for Data exchange;

Specifications

| Hardware Specification | Description |
|------------------------|--|
| Ports Type | 16 × 1000Mbps PoE ports (RJ45)+2 × 1000Mbps ports(RJ45)+2 × 1000Mbps ports (SFP) |

| | |
|------------------------|---|
| Standards | IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at |
| Switching capacity | 40Gbps |
| MAC | 8K |
| Packet Buffer | 4M bit |
| Forwarding performance | 29.76Mpps |
| Power supply | AC: 100-240V, 50/60Hz |
| PoE | support POE |
| Max. PoE Power | Max capacity:185W; Max capacity for single port: 30W |
| Cooling Fans | 1 |
| Weight | <4.2kg |
| Indicator | PWR(Green), LNK/ACT(Green), PoE(Orange) |
| Storage Temperature | -40 ° C ~ 70 ° C |
| Operating temperature | 0 ° C ~ 40 ° C (32 ° F ~ 104 ° F) |
| Operating humidity | 10%~90% (noncondensing) |
| Storage humidity | 5%~90% (noncondensing) |
| Dimensions (W×D×H) | 280mm x 180mm x 44mm (11"×7.1"×1.7") |
| Working Mode | Default(Normal mode) : All ports can communicate with each other.; VLAN(Secure mode): Downlink ports can communicate only with uplink ports.; Extend(Surveillance mode): Transmission distance up to 250 meters. Downlink ports can communicate only with uplink ports. |

Ordering Info

| Product Model | Description |
|------------------------|----------------------|
| NSW2010-18GT2GP-POE-IN | Ethernet Switch(POE) |

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2023-2024 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.