


# SF/UTP Category 6 Cables

CAB-LC3200A-IN



## Specifications

|                       |                                   |
|-----------------------|-----------------------------------|
| Model                 | CAB-LC3200A-IN                    |
| Cable                 |                                   |
| Product model         | CAB-LC3200A-IN                    |
| Test Standard         | ISO/IEC11801、TIA-568-C.2、YD/T1019 |
| Product specification | HSYV-6 4×2×0.585                  |
| Packing length        | 305±1m                            |
| Ambient temperature   | -20℃~60℃                          |
| Rip-cord              | Yes                               |
| Crossing backbone     | Yes                               |
| Conductor             |                                   |
| AWG                   | 23                                |
| Nom.O.D.(mm)          | 0.585±0.05 mm                     |
| DC resistance         | ≤65.8 Ω/km                        |
| Insulation            |                                   |
| Material              | HDPE                              |

|                         |  |
|-------------------------|--|
| Thickness               | 0.2±0.02 mm  |
| Diameter                | 1.16±0.05 mm   |
| Color                   | Blue/White- Blue,Green/White-Green,Orange/White-Orange,Brown/White-Brown |
| <b>Pitch</b>            |  |
| Offset pitch            | ≤20 mm   |
| Cable pitch             | ≤120 mm  |
| <b>Sheath</b>           |  |
| Material                | PVC(complies RoHS/REACH)   |
| Thickness               | 0.6±0.05 mm  |
| External O.D.           | 7.6±0.4 mm   |
| Tensile strength        | >13.5 Mpa  |
| Color                   | Black  |
| <b>Surface Printing</b> |  |
| Letter height           | 3.0±0.3 mm   |
| Color                   | White  |
| Print error / Space     | 1±0.005 m  |
| Case number             | Yes  |
| <b>Packing</b>          |  |
| Packing                 | Wooden shaft   |

## Ordering Info

| Product Model  | Description               |
|----------------|---------------------------|
| CAB-LC3200A-IN | Cat6(Shielded),305m,Black |

### Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

\*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.