

UTP Category 6 Cables

CAB-LC3100A-E2-ECA-IN



사양

Model	CAB-LC3100A-E2-ECA-IN
Cable	
Product model	CAB-LC3100A-E2-ECA-IN
Test Standard	ISO/IEC11801, TIA-568-C.2, Fluke Test 90m (channel)
Product specification	Cat6 4×2×0.50mm, CPR ECA
Packing length	305±1m
Crossing backbone	Yes
Rip-cord	Yes
Ambient temperature	-20°C to 60°C
Conductor	
Material	Solid-Bare Copper
AWG	24
Nom.O.D.(mm)	0.5±0.01 mm
DC resistance	≤95 Ω/km
Insulation	
Material	HDPE
Diameter	0.93±0.05 mm
Color	Blue/White- Blue, Green/White-Green,Orange/White-Orange,Brown/White-Brown
Sheath	
Material	LSZH (CPR Eca)
External O.D.	5.8±0.3 mm

Tensile strength	>10 Mpa
Thickness	0.6±0.05 mm
Color	Orange (RAL2008)
Surface Printing	
Color	Black
Letter height	3.0±0.3 mm
Print error / Space	1±0.005 m
Packing	
Packing	Carton
Once packing dimension	410mm*210mm*410mm
Twice packing dimension	430mm*465mm*430mm
Twice packing quantity	2

Unlimited New View

浙江宇视科技有限公司



<http://www.uniview.com>



overseasbusiness@uniview.com; globalsupport@uniview.com



South Tower, Building 10, Wanlun Science Park, 88 Jiangling Road, Hangzhou, P.R.China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

虽然我司试图在本资料中提供准确的信息，但不保证资料的内容不含有技术性误差或印刷性错误，为此我司对本资料中的不准确不承担任何责任。我司保留在没有通知或提示的情况下对本资料的内容进行修改的权利。