

# Ethernet Switches

## NSW2010-10T-POE-IN



### Features

- Multiple working modes to address your business needs: Default(Normal mode), VLAN(Secure mode), EXTEND(Surveillance mode)
- Support port traffic control
- Support for secure mode, all downlink ports can communicate only with uplink ports
- Up to 250m transmission distance on surveillance mode
- Support buffer optimization
- All metal housing, safe and reliable

### Specifications

Hardware Specification	Description
Ports Type	10 × 100Mbps network ports (RJ45), including 8 PoE ports

Forwarding performance	1.49Mpps
Standards	IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at
Switching capacity	2Gbps
Packet Buffer	1.625Mbit
MAC	4K
Power supply	AC: 100-240V, 50/60Hz
Max. PoE Power	Max capacity:120W; Max capacity for single port: 30W
Cooling Fans	0
Mean Time Between Failure (M TBF)	>50000 hours
Weight	<1.22kg
Operating humidity	10%~90% (noncondensing)
Storage humidity	5%~90% (noncondensing)
Operating temperature	0 ° C ~ 40 ° C (32 ° F ~ 104 ° F)
Storage Temperature	-40 ° C ~ 70 ° C
Dimensions (W×D×H)	220mm x 150mm x 44mm(8.7"×5.9"×1.7")
Working Mode	Default(Normal mode) : All ports can communicate with each other.; EXTEND(Surveillance mode): Transmission distance up to 250 meters.
Indicator	POWER Steady on: AC input is normal; POWER Off: No AC input; PoE Off: No PoE power supply; PoE Steady on: PoE power supply is normal; LINK/ACT Off: No link; LINK/ACT Steady on: Linked; LINK/ACT Flashing: Transmitting data; Speed Off: Linked at 10/100Mbps; Speed On: Linked at 1000Mbps

## Ordering Info

Product Model	Description
NSW2010-10T-PoE-IN	Ethernet Switch(PoE)

### Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: [overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)

<http://www.uniview.com>

©2023-2024 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

\*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.