

# PWR-550A-AC-NB datasheet

## PWR-550A-AC-NB



## Features

- 550W AC power module support for 1+1 redundant backup, hot plug and load flow sharing

## Specifications

Model	PWR-550A-AC-NB
Power	
Indicator light	<p>Output ON and OK : Green</p> <p>No AC power to all power supplies : OFF</p> <p>AC present/Only 12Vsb on (PS off) : 1Hz Blink Green</p> <p>AC present / Only 12VSB on (PS off) or PS in Smart on state</p> <p>AC cord unplugged or AC power lost; with a second power supply in parallel still with AC input power</p> <p>Power supply warning events where the power supply continues to operate; high temp, high power, high current, slow fan: 1Hz Blink Orange</p> <p>Power supply critical event causing a shutdown: UVP, OVP, OCP, OTP、 Fan fault、 short out : Orange</p> <p>Power supply critical event causing a shutdown; failure, OCP, OVP, Fan Fail: Orange</p>
AC Input Voltage	90-264VAC
AC Input Frequency	47 Hz-63 Hz
AC Input current	~100-240V,50/60Hz,7.0A
Power Working Temperature	0°C ~ 50°C
Power Storage Temperature	-40°C ~ 70°C

## Ordering Info

Product Model	Description
PWR-550A-AC-NB	550W AC Power Module

### Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: [overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)

<http://www.uniview.com>

©2024-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

\*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.