

VS-R5220-B2T@N-IN General-Purpose Mid-Range CPU Server

Datasheet

VS-R5220-B2T@N-IN



Overview

This high-end 2-socket 2U rack server is designed based on 2nd-generation Intel® Xeon® Scalable processors. It uses high-performance Intel® C620 series chipsets to deliver robust performance in a limited space and meanwhile provide scalability and high availability.

Features

- High performance
- The 2nd-generation Intel® Xeon® Scalable series processors provide strong processing power to deal with heavy computing load.
- 2 standard Gigabit network interfaces for data transmission, 1 optional dual-Gigabit or dual-10GE network interface module for expansion, capable of load balance, link aggregation and redundancy to effectively reduce network latency; 1 Gigabit remote management network interface.
- DDR4 3200Mhz RAM frequency, 16 RAM slots.
- High reliability
- The smart cooling system effectively reduces noises and creates a constant temperature in the chassis; the fully shielded design prevents electromagnetic radiation, anti-interference, and anti-static (EMI).
- Optional 1+1 power redundancy design supports PMBus, module-loss alarm and more to enhance server operation security.
- Low power consumption
- Supports frequency reduction to reduce system power consumption at low system load.
- Adjusts fan speed according to the temperature of thermally critical components to save energy, reduce noise, and improve reliability of fans.
- Supports PDCM (power efficiency manager) to provide automated server power consumption control to complete more tasks with less resources.

Specifications

Model	VS-R5220-B2T@N-IN
Hardware Parameters	
CPU	Intel® 4210R Xeon*2, support 2*2nd-generation Intel® Xeon® Scalable processors.
RAM	Standard 32G*2, total 16 slots
Standard HDD	4T SATA HDD*1
Front HDD expansion	12*2.5/3.5-inch SAS/SATA/SSD HDD (directly connected to backplane)
Network interface	GE*2, supports OCP or PCIe network interface expansion
Management	1 independent 1000Mbps network interface for IPMI remote management
USB	5*USB 3.0 (3 back, 2 front)
VGA	2*VGA interfaces (1 back, 1 front)
PCI-E card slots	6*PCI-E 3.0 slots
Built-in RAID controller	1 (sold separately)
Power supply	1+1 redundancy
Dimensions	87mm(H)x438mm(W)x735mm(D)
Power input	220V AC 240V DC
Weight	27KG (fully loaded)
Environment temperature	Operating: 10°C to 35°C Non-operating: -40°C to 55°C
Relative humidity	Non-operating: 95% (noncondensing at 25°C to 30°C)

Ordering Info

Product Model	Config	Description
VS-R5220-B2T	N-IN	2U Universal Mid-end CPU Server

Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



overseasbusiness@uniview.com; globalsupport@uniview.com



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China
(Zhejiang) Pilot Free Trade Zone, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.