

Ethernet POE Switches Datasheet

NSW2020-16T1GT1GC-POE-IN



Features

- Multiple working modes to address your business needs: Default(Normal mode), VLAN(Secure mode), EXTEND(Surveillance mode)
- Support port traffic control
- Support for secure mode, all downlink ports can communicate only with uplink ports
- Up to 250m transmission distance on surveillance mode
- Support buffer optimization
- All metal housing, safe and reliable

Specifications

Model	NSW2020-16T1GT1GC-POE-IN
Hardware Specification	
Ports Type	16×100Mbps PoE ports (RJ45)+ 1×1000Mbps Gigaethernet ports +1×1000Mbps Combo ports
Switching capacity	7.2 Gbps
Packet Buffer	4 M bit
MAC	16K
Forwarding performance	5.36Mpps
Prior Ports	1 to 8
Standards	IEEE802.3, IEEE802.3u, IEEE802.3z, IEEE802.3ab, IEEE802.3x, IEEE802.3af, IEEE802.3at, IEEE802.3az
Power Supply	AC: 100 to 240V, 50/60Hz
PoE Standard	IEEE 802.3 at, IEEE 802.3af
PoE Mode	ModeB (4578)

Max.PoE Power	Max capacity:250W Max capacity for single port: 30W
Max.Power	265W
Cooling Fans	1
Dimensions (W×D×H)	440*195*44mm
Operating Temperature	0°C to 40°C (32°F to 104°F)
Operating Humidity	10% to 90% (noncondensing)
Indicator	POWER: Steady on: AC input is normal Off: No AC input PoE: Off: No PoE power supply Steady on: PoE power supply is normal PoE-MAX: off : The POE power supply power of the whole machine is less than 80% of the specification Steady on : The POE power supply power of the whole machine is greater than 85% of the specification LINK/ACT: Off: No link Steady on: Linked Flashing: Transmitting data
Weight	2.12KG
Working Mode	Default (Normal mode) : All ports can communicate with each other, VLAN (Secure mode): Downlink ports can communicate only with uplink ports. Enabling PD keepalive function, the switch will restart the IPC via PoE power when the IPC sends no message in a period of time, Extend (Surveillance mode): Transmission distance up to 250 meters. Downlink ports can communicate only with uplink ports

Ordering Info

Product Model	Description
NSW2020-16T1GT1GC-POE-IN	Unmanaged Ethernet Switch(PoE)

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.