

Indoor Station

OEI-372S-H-W-Z



Overview

OEI-372S-H-W-Z indoor station is one of the terminals in the digital building intercom system, with functions of video intercom, security alarm, network camera monitoring, etc., providing a safe and comfortable living environment for residents. It can be widely used in building systems such as smart communities and parks.

Features

- Durable ABS casing with a glass panel.
- 1024×600 HD touchscreen display.
- Batch configuration and transfer.
- Remote and one-touch unlocking of linked door stations.
- Network camera monitoring and security alarm.

Specifications

| Model | OEI-372S-H-W-Z |
|------------------------|---|
| Hardware Specification | |
| Power Supply | DC12V±25%,IEEE802.3af, Standard PoE |
| Power Consumption | <10W |
| Screen | 7-inch ultra-thin TFT LCD screen |
| Screen Resolution | 1024×600 |
| Operation System | Linux |
| Audio Quality | Noise suppression,echo cancellation and AGC |
| Audio Input | 1 built-in omnidirectional microphone |

Unlimited New View

Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



overseasbusiness@uniview.com; globalsupport@uniview.com



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.