


4MP LightHunter HD IR Fixed Turret Analog Camera UAC-T124-AF28(40)LM



Overview

UAC-T124-AF28(40)LM is a 4MP LightHunter HD IR fixed turret analog camera with a high-performance 1/3-inch CMOS sensor. It supports TVI/AHD/CVI/CVBS, which effectively enhances product adaptability and diversity of networking solutions. With SYV-75-3 or other coaxial cable types, the camera can achieve low-cost, long-distance, and anti-interference mega-pixel HD video transmission without time delay. It supports IR-cut filter with auto-switch (ICR) and provides color images at daytime and black/white images at night. The camera also supports audio input and synchronous transmission of audio and video.

Features


- High quality imaging with 4MP resolution
- TVI/AHD/CVI/CVBS
- Supports IR-cut filter with auto-switch (ICR)
- LightHunter monitoring with high-sensitivity sensor
- Supports 180° horizontal flip, 180° vertical flip
- OSD configuration menu, easy to operate
- IP67 waterproof and dustproof design, high reliability
- OSD configuration menu in 11 languages
- Built-in microphone for high quality audio transmission via coaxial cables
- 3-Axis

Specifications

Model	UAC-T124-AF28LM		UAC-T124-AF40LM
Camera			
Max Resolution	4 MP		
Sensor Size	1/3.0" CMOS		
Min. Illumination	0.005 lux (F1.6, AGC ON) 0 lux (IR on)		
Lens			
Focus	2.8 mm	4.0 mm	
Lens Mount	M12		
Angle of View (H)	97.7°	81.1°	
Angle of View (V)	54.9°	41.0°	
Angle of View (D)	111.9°	94.4°	
Illuminator			
Illuminator Number	Two IR illuminators		
Illumination Distance	40m		
Lifetime	≥ 60000 hours		
Video			
Resolution	4MP: 2560 (H) × 1440 (V) 1080P: 1920 (H) × 1080 (V)		
Frame Rate	TVI: 4MP@25fps (default), 4MP@30fps,1080P@25fps, 1080P@30fps AHD: 4MP@25fps, 4MP@30fps,1080P@25fps, 1080P@30fps CVI: 4MP@25fps, 4MP@30fps,1080P@25fps, 1080P@30fps CVBS: PAL, NTSC		
Shutter Time	PAL: 1/25s-1/50000s, NTSC: 1/30s-1/50000s		
Image			
Exposure Mode	Four modes: Global (default), BLC, HLC, DWDR		
Day/Night	Three modes: Auto (default), Day, Night		
Digital Noise Reduction	2D		
White Balance	Two modes: Auto (default), Manual		
WDR	DWDR		
Smart IR	Support		
Flip	Supports 180°horizontal flip, 180°vertical flip		
Digital Defog	N/A		
Audio			
Built-in Mic	Support		
Camera Audio	TVI: 4MP@25fps, 4MP@30fps,1080P@25fps, 1080P@30fps CVI: 4MP@25fps, 4MP@30fps		
Interface			
Power Interface	5.5 mm Power Interface		
Video Output	BNC, supports TVI/AHD/CVI/CVBS		

Operating Environment	
Temperature	-30°C to 60°C (-22°F to 140°F)
Humidity	≤ 95% RH (non-condensing)
Surge Protection	4 KV for power, 4 KV for video output interfaces
Ingress Protection	IP67
General	
Power	DC 12 V ± 25%
Power Consumption	MAX 3.5W
Mount	Wall Mount, Pole Mount, Corner Mount, Pendant Mount
Dimensions	Φ111mm*98mm (diameter*height)
Material	Graphene + Metal + Plastic
Weight	334g(0.74lb)

Dimensions



Accessories

TR-JB03-G-IN Junction Box for Mini Fix-dome(Support wiring from behind)	TR-SE24-A-IN Dome Pendent Mounting Pole 500mm	TR-SE24-IN Dome Pendent Mounting Pole 200mm
		
TR-CM24-IN Dome Pendent Mounting Bracket(Indoor)	TR-A01-IN NPT 3/4" Waterproof Cable Gland	TR-JB07/WM03-G-IN-V2 Wall Mounting Assembling Bracket For 32 Fix-dome&Mini Fix-dome&Plastic Turret Camera
		
TR-WM03-D-IN-V2 Wall Mounting Bracket for 32 Fix-dome&Mini Fix-dome&Plastic Turret Camera	TR-UC08-C-V2 Bullet&Dome Corner Mounting Bracket	TR-UP06-C-IN-V2 Pole Mounting Bracket for Bullet Junction Box Only
		
PWR-DC1201A-UK DC12V/1A Wall Plug British Standard Power Adapter	PWR-DC1201B-UK UNV DC12V/1A Wall Plug British Standard Power Adapter(Colorful Bag)	PWR-DC1201A-US DC12V/1A Wall Plug American Standard Power Adapter
		
PWR-DC1201B-US UNV DC12V/1A Wall Plug American Standard Power Adapter(Colorful Bag)	PWR-DC1201A-EU DC12V/1A Wall Plug European Standard Power Adapter	PWR-DC1201B-EU UNV DC12V/1A Wall Plug European Standard Power Adapter(Colorful Bag)
		

PWR-DC1201A-IND UNV DC12V/1A Wall Plug Indian Standard Power Adapter-Colorful Bag		
		

Unlimited New View

Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



overseasbusiness@uniview.com; globalsupport@uniview.com



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.