

# 2MP ColorHunter HD Fixed Mini Bullet Analog Camera

UAC-B122-AF28(40)M-W



## Overview

UAC-B122-AF28(40)M-W is a 2MP ColorHunter HD fixed mini bullet analog camera with a high-performance 1/2.9-inch CMOS sensor. It supports TVI/AHD/CVI/CVBS, which effectively enhances product adaptability and diversity of networking solutions. With SYV-75-3 or other coaxial cable types, the camera can achieve low-cost, long-distance, and anti-interference mega-pixel HD video transmission without time delay. It supports audio input, synchronous transmission of audio and video, and provides 24/7 color images.

## Features


- 2MP high quality imaging
- TVI/AHD/CVI/CVBS
- Supports white light illumination, 24/7 color images
- Supports 180 horizontal flip, 180 vertical flip
- OSD configuration menu, easy to operate
- IP67 waterproof and dustproof design, high reliability
- OSD configuration menu in 11 languages
- Built-in microphone for high quality audio transmission via coaxial cables
- Supports digital defog
- Metal front face and housing

## Specifications

Sensor	Description
Pixel	UAC-B122-AF28M-W:2MP
Sensor Size	UAC-B122-AF28M-W:1/2.9" CMOS
Min. Illumination	UAC-B122-AF28M-W:0.005 lux (F1.6, AGC ON) 0 lux (white light on)
Lens	Description
Focus	UAC-B122-AF28M-W:2.8 mm
Lens Mount	UAC-B122-AF28M-W:M12
Angle of View (H)	UAC-B122-AF28M-W:101.5°
Angle of View (V)	UAC-B122-AF28M-W:56.9°
Angle of View (D)	UAC-B122-AF28M-W:117.4°
Illuminator	Description
Illuminator Number	UAC-B122-AF28M-W:Two white-light illuminators
Illumination Distance	UAC-B122-AF28M-W:40m
Lifetime	UAC-B122-AF28M-W:≥60000 hours
Video	Description
Resolution	UAC-B122-AF28M-W:1080P: 1920(H)×1080(V) 720P: 1280(H) × 720(V)
Frame Rate	UAC-B122-AF28M-W:TVI: 1080P@25fps (default), 1080P@30fps; 720P@25fps, 720P@30fps AHD: 1080P@25fps, 1080P@30fps; 720P@25fps, 720P@30fps CVI: 1080P@25fps, 1080P@30fps; 720P@25fps, 720P@30fps CVBS: PAL, NTSC
Shutter Time	UAC-B122-AF28M-W:PAL: 1/25s-1/50000s, NTSC: 1/30s-1/50000s
Image	Description
Exposure Mode	UAC-B122-AF28M-W:Four modes: Global(default), BLC, HLC, DWDR
Day/Night	UAC-B122-AF28M-W:24/7 color images
Digital Noise Reduction	UAC-B122-AF28M-W:2D/3D
White Balance	UAC-B122-AF28M-W:Two modes: Auto (default), Manual
WDR	UAC-B122-AF28M-W:DWDR

Flip	UAC-B122-AF28M-W:Supports 180°horizontal flip, 180°vertical flip
Digital Defog	UAC-B122-AF28M-W:Support
<b>Audio</b>	Description
Built-in Mic	UAC-B122-AF28M-W:Support
Camera Audio	UAC-B122-AF28M-W:TVI: 1080P@25fps, 1080P@30fps CVI: 1080P@25fps, 1080P@30fps
<b>Interface</b>	Description
Power Interface	UAC-B122-AF28M-W:5.5 mm Power Interface
Video Output	UAC-B122-AF28M-W:BNC, supports TVI/AHD/CVI/CVBS
<b>Operating Environment</b>	Description
Temperature	UAC-B122-AF28M-W:-30 °C ~ 60 °C (-22 °F ~ 140 °F)
Humidity	UAC-B122-AF28M-W:≤95% RH (non-condensing)
Surge Protection	UAC-B122-AF28M-W:4kV for power; 4kV for video output interfaces
Ingress Protection	UAC-B122-AF28M-W:IP67
<b>General</b>	Description
Power	UAC-B122-AF28M-W:DC12V ± 25%
Power Consumption	UAC-B122-AF28M-W:MAX 3.12W
Mount	UAC-B122-AF28M-W:Corner Mount; Pole Mount
Dimensions	UAC-B122-AF28M-W:157mm*67mm*66mm (L*W*H)
Material	UAC-B122-AF28M-W:Metal
Weight	UAC-B122-AF28M-W:279g(0.62lb)

# Dimensions


**Zhejiang Uniview Technologies Co., Ltd.**

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China (Zhejiang) Pilot Free Trade Zone, China

Email: [overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)

<http://www.uniview.com>

©2023-2024 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

\*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.